



**SUMMARY TEST DATA
ON
APD-2-0D82D2-SFF-30W**

Customer: _____
SO No: _____
Model No: APD-2-0D82D2-SFF-30W
Serial No: PL56740/2548

Tested By: K Craven
Temperature: +25 C
Date: 11/24/2025
Drawing No: 27644900 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range	0.8 to 2.2 GHz	0.8 to 2.2 GHz	PMI QA2	
2	Insertion Loss	0.5 dB MAX (Above 3.01 dB Split)	0.3 dB (See Plot)		
3	Isolation	22 dB MIN.	27.6 dB (See Plot)		
4	VSWR	INPUT 1.20:1 MAX. OUTPUT 1.15:1 MAX.	INPUT 1.12:1 OUTPUT 1.09:1 (See Plot)		
5	Amplitude Balance	±0.1 dB MAX	0.03 dB MAX. 0 dB MIN. (See Plot)		
6	Phase Balance	±2° MAX	0° MAX. -1.05° MIN. (See Plot)		PMI QA2



* FOR ALL OTHER SPECIFICATIONS PLEASE SEE TYPICAL CHARACTERISTICS ON THE PMI WEBSITE
Note: Amplitude and phase balance are relative to J1 Port.

QA/QC Approval:   PMI QA2

Date: 11/26/2025





SUMMARY TEST DATA ON APD-2-0D82D2-SFF-30W





SUMMARY TEST DATA ON APD-2-0D82D2-SFF-30W





SUMMARY TEST DATA ON APD-2-0D82D2-SFF-30W

