



## SUMMARY TEST DATA ON LM-4G18G-100W-15DBM-SMF

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: LM-4G18G-100W-15DBM-SMF  
 Serial No: PL56933/2551

Tested By: K Craven  
 Temperature: +25°C  
 Date: 12/5/2025  
 Drawing No: 27645320      REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	4 GHz to 18 GHz	4 GHz to 18 GHz	PMI QA4
2	Insertion Loss: @ -10 dBm Input Power	2.5 dB Max. 2.6 dB Max. @ +55°C	2.44 dB See Graph	
3	VSWR: @ -10dBm Input Power	Input: 2.2:1 Max. Output: 2.2:1 Max.	2.06:1 In 2.05:1 Out See Graph	
4	Leakage Power: Flat	+15 dBm Max.	+ 9.43 dBm See Graph	
5	Input Power:	+50 dBm CW 100 W Max.	Pass See Typical Characteristics	
6	Peak Input Power:	+60 dBm CW 1 kW Max. 1% DC 1 us PW	Pass See Typical Characteristics	
7	Recovery Time:	100 ns Max.	Pass See Typical Characteristics	

QA/QC Approval: \_\_\_\_\_

Date: 12/12/2025

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731  
 Email: sales@pmi-rf.com

# SUMMARY TEST DATA ON LM-4G18G-100W-15DBM-SMF

