



## SUMMARY TEST DATA ON APD-3-218-SFF-30W

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: APD-3-218-SFF-30W  
 Serial No: PL57402/2603

Tested By: E. Kretz  
 Temperature: +25 C  
 Date: 1/20/2026  
 Drawing No: 27653320      Rev: A1

| TEST ITEM NO. | PARAMETERS        | SPECIFIED VALUE                     | TEST RESULTS              | QA QC      |
|---------------|-------------------|-------------------------------------|---------------------------|------------|
| 1             | Frequency Range   | 2 GHz – 18 GHz                      | 2 GHz – 18 GHz            | PMI<br>QA2 |
| 2             | Insertion Loss    | 1.6 dB MAX<br>(ABOVE 4.77 dB SPLIT) | 1.08 dB<br>See Graph      |            |
| 3             | VSWR              | INPUT:<br>1.65:1 MAX                | 1.57:1<br>See Graph       |            |
|               |                   | OUTPUT:<br>1.65:1 MAX               | 1.54:1<br>See Graph       |            |
| 4             | Isolation         | 20 dB MIN                           | 21 dB<br>See Graph        |            |
| 5             | Amplitude Balance | ±0.7 dB MAX                         | 0.2 dB MAX                |            |
|               |                   |                                     | -0.27 dB MIN<br>See Graph |            |
| 6             | Phase Balance     | ±9.0° MAX                           | -2.52° MAX                | PMI<br>QA2 |
|               |                   |                                     | 2.52° MIN<br>See Graph    |            |

\* FOR ALL OTHER SPECIFICATIONS, PLEASE SEE TYPICAL CHARACTERISTICS ON THE PMI WEBSITE

QA/QC Approval:       PMI  
QA2

Date: 1/30/2026

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 Email: sales@quanticpmi.com



