



**SUMMARY TEST DATA
ON
P2T-218-60-512-R-SFF**

Customer: _____
 SO No: _____
 Model No: P2T-218-60-512-R-SFF
 Serial No: PL58438/2611

Tested By: A. Mousavi
 Temperature: +25° C
 Date: 3/7/2026
 Drawing No: 27648420 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	2.0 GHz to 18.0 GHz	2.0 GHz to 18.0 GHz	PMI QA6	
2	Insertion Loss:	1.8 dB Max.	1.69 dB See Graph		
3	Isolation:	60 dB Min.	61.2 dB See Graph		
4	VSWR:	1.9:1 Max.	1.86:1 In 1.77:1 Out See Graph		
5	Switching Speed:	30 ns Max.	20 ns See Typical Characteristics		
7	DC Supply:	+5 VDC @ 65 mA Max. -12 VDC @ 65 mA Max.	+5 VDC @ 20 mA -12 VDC @ 20 mA		PMI QA6

QA/QC Approval: *Anthony Kardis* PMI
QA6

Date: 3/13/26

**SUMMARY TEST DATA
ON
P2T-218-60-512-R-SFF**

