



SUMMARY TEST DATA
ON

P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM

Customer: _____
 SO No: _____
 Model No: P1T-DC40G-65-T-292FF-1NS-OPT18G-50OHM
 Serial No: PL58972/2615

Tested By: OLIVER K
 Temperature: 25°C
 Date: 4/8/2026
 Drawing No: 27630283 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	DC to 18 GHz	DC to 18 GHz	PMI QAS
2	Isolation	55 dB Min. 60 dB Typ.	60.1 dB	
3	Insertion Loss	5 dB Max. 4.5 dB Typ.	3.56 dB	
4	VSWR: In/Out	2.2:1 Max. 2:1 Typ.	1.48:1 In 1.58:1 Out	
5	Input Power	17 dBm CW Max Operating	Pass See Typical Characteristics	
6	Switching Speed	7 ns Max. 6 ns Typ.	Pass See Typical Characteristics	
7	Rise/Fall Time	2 ns Max. Rise 1 ns Typ. Rise 2 ns Max. Fall 1 ns Typ. Fall	Pass See Typical Characteristics	
8	Control Signal	TTL LOGIC '1' : Insertion Loss '0' : Isolation	Pass	
9	Video Transients	300 MHz BW (2 to 18 GHz): 85 mv P-P 20 MHz BW (2 to 18 GHz): 15	Pass See Typical Characteristics	
10	Power Supply	8 to 15 V @ 15 mA -8 to -15 V @ 40 mA	15 V @ 10 mA -15 V @ 30 mA	

QA/QC Approval: *Jordan Sygal*

Date: 4.17.26

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@quanticpmi.com



