



**SUMMARY TEST DATA  
ON  
PEC-100M6G-3T-SFF-ROHS**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: PEC-100M6G-3T-SFF-ROHS  
 Serial No: PL59553/2618

Tested By: Darwin Martinez-C.  
 Temperature: 25°C  
 Date: 4/29/2026  
 Drawing No: 27353900 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.1 GHz to 6 GHz	0.1 GHz to 6 GHz	<i>PMI QA5</i>
2	Insertion Loss	2 dB Max. @ 640MHz	1.21 dB	<i>PMI QA5</i>
3	VSWR: In/Out	2:1 Max.	1.39:1 In 1.31:1 Out	
4	Isolation	70 dB Min.	72.2 dB	
5	P1dB	23 dBm Min	Pass See Typical Characteristics	
6	Switching Speed	100 ns Max.	Pass See Typical Characteristics	
7	Power Supply	5 V @ 250 mA Max. -12 V @ 120 mA Max.	5 V @ 68 mA -12 V @ 38 mA	
8	Control Signal	TTL LOGIC SEE TRUTH TABLE	Pass	

TRUTH TABLE		
TTL1	TTL2	PATH
0	0	J1-J4
0	1	J2-J4
1	0	J3-J4
1	1	UNDEFINED

QA/QC Approval: *J. P. ...* Date: 4-30-26

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 Email: sales@pmi-rf.com



