



**SUMMARY TEST DATA
ON
P2T-218-60-R-1W-SFF**

Customer: _____
 SO No: _____
 Model No: P2T-218-60-R-1W-SFF
 Serial No: PL60176/2621

Tested By: Adriana M. / Anuar Polania
 Temperature: +25° C
 Date: 5/20/2026
 Drawing No: 26943760 Rev: B4

| TEST ITEM NO. | PARAMETERS | SPECIFIED VALUE | TEST RESULTS | QA QC |
|---------------|------------------------|---|--|-------|
| 1 | Frequency Range: | 2.0 GHz to 18.0 GHz | 2.0 GHz to 18.0 GHz | |
| 2 | Insertion Loss: | 2.5 dB Max. | 1.8 dB See Graph | |
| 4 | Isolation: | 60 dB Min. | 60.4 dB See Graph | |
| 5 | VSWR: | 2.0:1 Max. | 1.79:1 In 1.81:1 Out See Graph | |
| 6 | Switching Speed: | 25 ns Max. | 20 ns See Typical Characteristics | |
| 3 | Operating Input Power: | 1 Watt CW Max. 2W Pk, 1% DC, 100ns Max. | Pass See Typical Characteristics | |
| 7 | DC Supply: | +5 to +15 VDC @ 65 mA Max.. -5 to -15 VDC @ 65 mA Max. | +5 to +15 VDC @ 14 mA -5 to -15 VDC @ 19 mA | |
| 8 | Control: | Logic Table | | |
| | | CTL1 | Function | |
| | | 0 | J1-J2 | |
| | | 1 | J1-J3 | |

QA/QC Approval: *Jordan Reed*

Date: 5/21/26

**SUMMARY TEST DATA
ON
P2T-218-60-R-1W-SFF**

