



## SUMMARY TEST DATA ON P2T-218-60-R-1W-SFF

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P2T-218-60-R-1W-SFF  
 Serial No: PL60180/2621

Tested By: Adriana M. / Anuar Polania  
 Temperature: +25° C  
 Date: 5/20/2026  
 Drawing No: 26943760 Rev: B4

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2.0 GHz to 18.0 GHz	2.0 GHz to 18.0 GHz	PMI QAS
2	Insertion Loss:	2.5 dB Max.	1.8 dB See Graph	
4	Isolation:	60 dB Min.	60.5 dB See Graph	
5	VSWR:	2.0:1 Max.	1.89:1 In 1.89:1 Out See Graph	
6	Switching Speed:	25 ns Max.	20 ns See Typical Characteristics	
3	Operating Input Power:	1 Watt CW Max. 2W Pk, 1% DC, 100ns Max.	Pass See Typical Characteristics	
7	DC Supply:	+5 to +15 VDC @ 65 mA Max. -5 to -15 VDC @ 65 mA Max.	+5 to +15 VDC @ 14 mA -5 to -15 VDC @ 19 mA	
8	Control:	Logic Table		
		CTL1	Function	
		0	J1-J2	
		1	J1-J3	

QA/QC Approval: *Jordan Syed*

Date: 5/21/26

**SUMMARY TEST DATA  
ON  
P2T-218-60-R-1W-SFF**

