



**SUMMARY TEST DATA
ON
P2T-218-60-R-1W-SFF**

Customer: _____
 SO No: _____
 Model No: P2T-218-60-R-1W-SFF
 Serial No: PL60184/2621

Tested By: Adriana M. / Anuar Polania
 Temperature: +25° C
 Date: 5/20/2026
 Drawing No: 26943760 Rev: B4

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	2.0 GHz to 18.0 GHz	2.0 GHz to 18.0 GHz	PMI QA5	
2	Insertion Loss:	2.5 dB Max.	1.77 dB See Graph	PMI QA5	
4	Isolation:	60 dB Min.	61.2 dB See Graph		
5	VSWR:	2.0:1 Max.	1.96:1 In 1.81:1 Out See Graph		
6	Switching Speed:	25 ns Max.	20 ns See Typical Characteristics		
3	Operating Input Power:	1 Watt CW Max. 2W Pk, 1% DC, 100ns Max.	Pass See Typical Characteristics		
7	DC Supply:	+5 to +15 VDC @ 65 mA Max.. -5 to -15 VDC @ 65 mA Max.	+5 to +15 VDC @ 13 mA -5 to -15 VDC @ 18 mA		
8	Control:	Logic Table			PMI QA5
		CTL1	Function		
		0	J1-J2		
		1	J1-J3		

QA/QC Approval: *Jordan Syed*

Date: 5/21/26

**SUMMARY TEST DATA
ON
P2T-218-60-R-1W-SFF**

