



SUMMARY TEST DATA
ON
P20T-4G8G-80-T-515-SFF

Customer: _____
SO No: _____
Model No: P20T-4G8G-80-T-515-SFF
Serial No: PL60875/2627

Tested By: A. Mousavi
Temperature: 25°C
Date: 6/27/2026
Drawing No: 27624423 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	4 GHz to 8 GHz	4 GHz to 8 GHz	PMI QA6
2	Isolation	80 dB Min.	81.7 dB	
3	Insertion Loss	4 dB Max.	3.99 dB	
4	VSWR: In/Out	2:1 Max. 1.8:1 Typ.	1.84:1 In 1.9:1 Out	
5	Operating Power CW	0.1 Watts Max (Hot Switchable)	Pass See Typical Characteristics	
6	Switching Speed Max	2000ns Max. (50% TTL to 90% RF) 2000ns Max. (10% RF to 90% RF)	Pass See Typical Characteristics	
7	Power Supply	5 V @ 300 mA Max. 15 V @ 200 mA Max.	5 V @ 135 mA 15 V @ 160 mA	PMI QA6

QA/QC Approval:

Anthony Brady
PMI
QA6

Date:

6/30/26



