



SUMMARY TEST DATA ON LM-10M18G-16-20W-AL-SFF

Customer: _____
SO No: _____
Model No: LM-10M18G-16-20W-AL-SFF
Serial No: PL60987/2627

Tested By: A. Mousavi
Temperature: +25°C
Date: 7/1/2026
Drawing No: 27647500 REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	10 MHz to 18.0 GHz	10 MHz to 18.0 GHz	PMI QA5
2	Insertion Loss:	2.0 dB Max. @ -10 dBm Input Power	1.61 dB See Graph	
3	Leakage Power:	+17dBm Max.	Pass See Typical Characteristics	
4	Impedance:	50 Ohms	Pass See Typical Characteristics	
5	Recovery Time (3 dB):	250 ns Max. @ 1 kW Peak Power	Pass See Typical Characteristics	
6	VSWR:	2.0:1 Max. @ -10 dBm Input Power	1.86:1 In 1.94:1 Out See Graph	
7	RF Power Handling:	20 W CW Max. @ -55° C TO +85° C	Pass See Typical Characteristics	
		100W Peak (10 μs PW, 10% DC)	Pass See Typical Characteristics	
8	Limiting Threshold:	+ 5 dBm Min. (1 dB Compression)	+ 8 dBm See Graph	PMI QA5

QA/QC Approval:

Joseph M. Szyja

Date:

7/18/26

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
Email: sales@pmi-rf.com

SUMMARY TEST DATA ON LM-10M18G-16-20W-AL-SFF

PL6/0987/2627

