

**SUMMARY TEST DATA
ON
P1T-200M18G-80-T-SFF-F192A-CTLSMA**

Customer: _____
SO No: _____
Model No: P1T-200M18G-80-T-SFF-F192A-CTLSMA
Serial No: PL61605/2633

Tested By: K Craven
Temperature: 25 Degrees C
Date: 8/10/2026
Drawing No: 27648560 Rev: A1



TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	0.2 - 18 GHz	0.2 - 18 GHz	PMI QA6
2	Insertion Loss:	3.5 dB Max	2.5 dB (See Plot)	
3	Isolation:	70 dB Min (0.2 - 0.5 GHz) 80 dB Min (0.5 - 18 GHz)	81.8 dB 88.8 dB (See Plot)	
4	VSWR: (J1 - "On Only") (J2 - "On or "Off")	2.0:1 Max	1.78 :1 (See Plot)	
5	Operating Power:	+27 dBm "Hot Switching" Max	Pass	
6	Switching Speed:	10 ns (Rise / Fall) 15 ns (Delay On) 30 ns (Delay Off)	<5 ns <5 ns <10 ns	
7	Control:	TTL Logic "0" = On TTL Logic "1" = Off	Pass	
8	DC Supply:	+5 VDC @ 50 mA Max -12 VDC @ 75 mA Max	10 mA 30 mA	PMI QA6

QA/QC Approval: _____

Anthony Kacoly

PMI
QA6

Date: 8/13/26



SUMMARY TEST DATA
ON
P1T-200M18G-80-T-SFF-F192A-CTLSMA

