



SUMMARY TEST DATA
ON
LM-1G18G-16-4W-SMF

Customer: _____
SOno: _____
Model No: LM-1G18G-16-4W-SMF
Serial No: PL61907/2634
Part No: _____

Tested By: John R. _____
Temperature: +25°C _____
Date: 8/24/2026 _____
Drawing No: 27634041 _____ REV: A2 _____

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	1.0 to 18.0 GHz	1.0 to 18.0 GHz	PMI QA6
2	Insertion Loss:	2.3 dB Max. @ -10 dBm Input Power	1.81 dB See Graph	
3	Leakage Power:	40 mW Max.	Pass See Typical Characteristics	
4	Spike Leakage:	0.1 erg. Max.	Pass See Typical Characteristics	
5	Recovery Time:	250 ns Max. @ 1000 W Peak Power	Pass See Typical Characteristics	
6	VSWR:	2.0: 1Max. @ -10 dBm Input Power	1.92:1 In 1.87:1 Out See Graph	
7	RF Power Handling:	4 W CW Max. @ 85°C	Pass See Typical Characteristics	PMI QA6
		1000 W Peak Max. (1 μ s PW, 0.1% DC @ 85°C)	Pass See Typical Characteristics	
8	Limiting Threshold:	+5 dBm Min. (1 dB Compression)	+8 dBm See Graph	

QA/QC Approval:


Anthony Kacoly PMI
QA6

Date: 8/25/26


SUMMARY TEST DATA ON LM-1G18G-16-4W-SMF

PL61907/2634

Insertion Loss



VSWR



Limiter Response with Frequency

