Quantic PMI
PLANAR MONOLITHICS

SUMMARY TEST DATA ON APD-4-20M6G-28V

Customer:
SO No:
Model No: APD-4-20M6G-28V
Serial No: PL62138/2635

Tested By: K. Wagaman
Temperature: +25°C
Date: 8/28/2026
Drawing No: 27624827 **Rev:** A2

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	20 MHz to 6 GHz	20 MHz to 6 GHz	PMI QA5
2	Gain:	3.5 dB ±2 dB Max.	3.42 dB (J1) ±1.14 dB 3.41 dB (J2) ±1.14 dB 3.44 dB (J3) ±1.16 dB 3.41 dB (J4) ±1.18 dB (See Graph)	
3	VSWR:	2.5:1 Max.	1.4:1 (J1) 1.4:1 (J2) 1.4:1 (J3) 1.4:1 (J4) 2.2:1 (J5) (See Graph)	
4	Noise Figure:	5.5 dB (70 to 3000 MHz) Max. 6 dB (20 to 6000 MHz) Typ.	Pass (See Typical Characteristics)	
5	Out Power P1dB:	10 dBm (20 to 2000 MHz) Typ. 9 dBm (3.0 to 6.0 GHz) Typ.	Pass (See Typical Characteristics)	
6	Input Power:	33 dBm Max. (Survival)	Pass (See Typical Characteristics)	
7	Power Supply:	+28V @ +200 mA Max.	85 mA	PMI QA5

QA/QC Approval: Jordan Lefed Date: 8/31/26

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com

Quantic PMI
PLANAR MONOLITHICS

SUMMARY TEST DATA ON APD-4-20M6G-28V

PL62138/2635









7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com