PLANAR MONOLITHICS

SUMMARY TEST DATA
ON
LM-28-C3-1

Customer:
SO No:
Model No: LM-28-C3-1
Serial No: PL62370/2638
Part No:

Tested By: John R.
Temperature: +25° C
Date: 9/15/2026
Drawing No: 27649960 REV: A1


TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	2 GHz to 8 GHz	2 GHz to 8 GHz	PMI QA8
2	Insertion Loss:	1.2 dB Max. @ -10 dBm Input Power	0.94 dB See Graph	
5	VSWR:	2.0:1 Max. @ -10 dBm Input Power	1.32:1 In 1.31:1 Out See Graph	
3	Leakage Power:	80 mW Typ. +19 dBm	Pass See Typical Characteristics	
4	Recovery Time :	1000 ns Typ @ 1 kW Peak. 100 ns Typ @ 3W CW	Pass See Typical Characteristics	
6	RF Power Handling:	3 W CW Max.	Pass See Typical Characteristics	
		1kW Peak Max 1µs Pulse Width, 1% Duty Cycle	Pass See Typical Characteristics	
7	Limiting Threshold:	+ 5 dBm Min. (1 dB Compression)	+ 9 dBm See Graph	PMI QA8


QA/QC Approval: PMI Date: 9/1 /26


7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
Email: sales@pml-rf.com

PL62370/2638

SUMMARY TEST DATA
ON
LM-28-C3-1







7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
Email: sales@pmi-rf.com