



**SUMMARY TEST DATA
ON
7CL9D66G-960-CD-SFF**

Customer: _____	Tested By: <u>S. PALACIO</u>
SO No: _____	Temperature: <u>+25°C</u>
Model No: <u>7CL9D66G-960-CD-SFF</u>	Date: <u>8/21/2014</u>
Serial No: <u>PL6325/0943</u>	
Part No: _____	

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	QA/QC
1	Center Frequency	9660 MHz Nom.	9660 MHz Nom. See Plot	
2	3 dB Pass band Bandwidth:	960 MHz Min.	960MHz See Plot	
3	Pass band VSWR	1.5:1 Max	1.30:1 See Plot	
4	Passband Insertion Loss:	5 dB Max	0.51dB See Plot	
5	Loss Ripple (peak-to-peak):	0.5 dB Max	0.1dB See Plot	
6	Rejection 70 dB:	DC – 7800MHz 11940 MHz 13750 MHz	95.37dB Min. See Plot	
7	Rejection 50 dB:	14500 – 17000 MHz 8350 MHz	70.64dB Min. See Plot	
8	Input Power:	+30 dBm Max	+30 dBm See Plot	
9	Impedance (Source Load)	50 ohms Nom.	Pass	

QA/QC Approval: _____ Date: _____



**SUMMARY TEST DATA
ON
7CL9D66G-960-CD-SFF**

