



**SUMMARY TEST DATA**

**ON AMPLIFIER**

Customer :  
 Job No :  
 Model No : POB-28-818-13-LCA  
 Serial No : PL6507

Tested By : Hugo Gonzales  
 Temperature : +25°C  
 Date : 11/03/09

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	REMARKS QA/QC
1	Frequency Range:	8.0-18.0 GHz	Pass	
2	Gain:	+28dB Typ.	Pass (See Plot)	
3	Gain Flatness:	±1.75dB Typ.	± 1.32dB	
4	VSWR:	Input : 2.0:1 Output: 2.0:1 (Typ.)	Pass (See Plot)	
5	Noise Figure:	3.0dB Typ.	Pass (See NF Plot)	
6	OP1dB:	13dBm Typ.	Pass	
7	DC Supply:	150mA@ +12 to +15VDC Max.	130mA@ +12 to +15VDC	


Production Manager Approval: \_\_\_\_\_ Date: \_\_\_\_\_

QA/QC Approval: \_\_\_\_\_ Date: \_\_\_\_\_

7311-F Grove Road, Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 email: sales@pmi-rf.com




### Swept S-Parameter Plot



7311-F Grove Road, Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
email: sales@pmi-rf.com



### Noise Figure Plot



7311-F Grove Road, Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
email: sales@pmi-rf.com