

**SUMMARY TEST DATA
ON
PTB-42-1G40G-12-292FF-
DC12**

81822

Customer: _____	Tested By: <u>J.Emperador</u>
Sales Order: _____	Temperature: <u>+25°C</u>
Model No: <u>PTB-42-1G40G-12-292FF-DC12</u>	Date: <u>01/21/2020</u>
Serial No: <u>PL81822</u>	Drawing No: <u>27616212</u> Rev: <u>A1</u>

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	QA/QC	
1	Frequency Range:	1.0 TO 40.0GHz	1.0 to 40.0 GHz (See Plot)	PMI QA 1	
2	Gain:	40dB Typ.	38.04 dB (See Plot)		
3	Gain Flatness	±2.5dB Typ.	2.31 dB (See Plot)		
4	Noise Figure:	5.0dB Typ. MID-BAND	Pass N/A		
5	OP1dB:	+22dBm Typ. (1-18GHz) +18dBm Typ. (18-40GHz)	Pass N/A		
6	VSWR In/Out:	2.5:1 Typ.	2.04:1/2.09:1 (See Plot)		
7	Maximum RF Input:	+15dBm	Pass		
8	AC Voltage Supply:	120VAC	120VAC		
9	DC Voltage Supply (External):	+12VDC	12VDC		PMI QA 1

QA/QC Approval:  PMI QA 1 Date: 1/23/20

**SUMMARY TEST DATA
ON
PTB-42-1G40G-12-292FF-
DC12**

81822

Gain Flatness and VSWR Plot

