

# SUMMARY TEST DATA ON P2T-500M18G-USB

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P2T-500M18G-USB  
 Serial No: 82077  
 Part No: \_\_\_\_\_

Tested By: K. Mansfield  
 Temperature: 25 Degrees C  
 Date: 12/3/2018  
 Drawing No: 27622530 Rev: B1

| TEST<br>ITEM NO | PARAMETERS       | SPECIFIED VALUE | TEST RESULTS                                | QA<br>QC    |
|-----------------|------------------|-----------------|---------------------------------------------|-------------|
| 1               | Frequency Range: | 0.5 to 18 GHz   | 0.5 to 18 GHz                               | PMI<br>QA 1 |
| 2               | Isolation:       | 60 dB Min.      | 66 dB<br>See Plot                           |             |
| 3               | Insertion Loss:  | 6.0 dB Max.     | 2.78 dB<br>See Plot                         |             |
| 4               | VSWR In/Out:     | 2.5:1 Typ.      | 1.95:1 In/Out<br>1.69:1 Out/Off<br>See Plot |             |
| 5               | Input Power:     | +20 dBm CW Max. | +20 dBm<br>See Typical Characteristics      |             |
| 6               | Power Connector: | USB Type A Plug | Pass                                        | PMI<br>QA 1 |

QA/QC Approval: \_\_\_\_\_

PMI  
QA 1

Date: \_\_\_\_\_

12/4/18

**SUMMARY TEST DATA  
ON  
P2T-500M18G-USB**

82077

