

**SUMMARY TEST DATA
ON
P2T-4G8G-70-T-SFF**

Customer: _____
 SO No: _____
 Model No: P2T-4G8G-70-T-SFF
 Serial No: 82087
 Part No: _____

Tested By: K. Mansfield
 Temperature: +25°C
 Date: 12/11/2018
 Drawing No: 27626442 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	4.0 GHz to 8.0 GHz	4.0 GHz to 8.0 GHz	PMI QA 1	
2	Insertion Loss:	1.9 dB Max.	1.81 dB See Plot		
3	Isolation:	70 dB Min.	92 dB See Plot		
4	VSWR: In/Out	1.6:1 Typ.	In 1.42:1 Out 1.47 :1 See Plot		
5	Switching Speed:	100 ns Max.	<100 ns See Typical Characteristics		
6	Input Power:	+30 dBm Max. (Survival) +20 dBm Max. (Operating)	Pass See Typical Characteristics		
7	DC Supply:	+5 VDC @ 100 mA Typ. -15 VDC @ 100 mA Typ.	+5 VDC @ 24 mA -15 VDC @ 57 mA		
8	Control Signal:	LOGIC TABLE CTL FUNCTION 0 J1-J2 "Low Loss" 1 J1-J3 "Low Loss"	Pass		PMI QA 1

QA/QC Approval: PMI
QA 1

Date: 12/11/18

**SUMMARY TEST DATA
ON
P2T-4G8G-70-T-SFF**

82087

