

**SUMMARY TEST DATA**  
**ON**  
**PS-360-3237-8-292FF**

Customer: \_\_\_\_\_  
 Job No: \_\_\_\_\_  
 Model No: PS-360-3237-8-292FF  
 Serial No: 92190  
 Part No: \_\_\_\_\_

Tested By: K. Mansfield  
 Temperature: +25°C  
 Date: Monday, May 06, 2019  
 Drawing No: 27617038 Rev: B1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	32 GHz to 37 GHz	32 GHz to 37 GHz	PMI QA 1	
2	Insertion Loss:	13.0 dB Typ.	15.6 dB See Plot		
3	VSWR Input: (J2)	2.0:1 Typ. 2.3:1 Max.	1.9:1		
4	VSWR Output: (J1)	2.5:1 Typ. 3.0:1 Max.	2.2:1		
5	Step Size: (LSB)	1.40625°	1.85947°		
6	Phase Shift: (Max.)	358.59375°	356.34308°		
7	Amplitude Error:	±1.50 dB Typ.	±1.55 dB		
8	Phase Shift Error:	±5.0° Typ.	+0.6° -1.6° See Plot		
9	Switching Speed: (10% to 90% of Phase Shift)	500 ns Max.	<300 ns See Typical Characteristics		
10	Voltage:	+15 V @ 90 mA Max. -15 V @ 60 mA Max.	+15 V @ 14 mA -15 V @ 9 mA		PMI QA 1

QA/QC Approval: 

PMI  
QA 1

Date: 5/6/19

**SUMMARY TEST DATA  
ON  
PS-360-3237-8-292FF**

92190

