DESCRIPTION

LOW NOISE AMPLIFIER DESIGNED FOR MILITARY AND INDUSTRIAL APPLICATIONS. THIS AMPLIFIER IS SUPPLIED IN OUR STANDARD PE2 HOUSING THAT CAN BE USED AS AN SMA CONNECTORIZED OR A SURFACE MOUNT COMPONENT. OTHER PACKAGES AND CONNECTOR TYPES ARE AVAILABLE. THIS MODEL PROVIDES THE FOLLOWING PERFORMANCE. DATA IS AVAILABLE UPON REQUEST.

SPECIFICATIONS

- FREQUENCY RANGE: 4.0 to 18.0 GHZ
- GAIN FLATNESS: ±1.0dB MAXIMUM
- NOISE FIGURE:
 4.0dB TYPICAL
- OP1dB:-----+24dBm MINIMUM
- OIP3: +34dBm MINIMUM
- CONNECTORS: SMA (F) REMOVABLE
- DC SUPPLY: +12 TO +15VDC @ 500mA NOMINAL
- SIZE——— (L) 1.08" X (W) 0.71" X (H) 0.29"
 - *EXCLUDING CONNECTORS*
- FINISH GOLD PLATED

FEATURES

- INTERNAL VOLTAGE REGULATION
- UNCONDITIONAL STABILITY

AVAILABLE OPTIONS

- VARIOUS PACKAGE TYPES
- VARIOUS CONNECTOR TYPES
- TEMPERATURE COMPENSATION
- GAIN AND PHASE MATCHING
- MIL-STD-883 SCREENING AVAILABLE

ENVIRONMENTAL RATINGS

- TEMPERATURE: -20°C TO + 70°C (OPERATING) -65°C TO +125°C (STORAGE)
- HUMIDITY: _____ MIL-STD-202F, METHOD 103B COND. B
- SHOCK: _____ MIL-STD-202F, METHOD 213B COND. B
- ALTITUDE: _____ MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES

TOLERANCES:


X.XX ±0.020

X.XXX ±0.010


REVISIONS										
ZONE	REV.	DESCRIPTION	DATE	APPROVED						
	1	PRELIMINARY	12/2/14							

MECHANICAL OUTLINE

PE2 HOUSING WITH CARRIER



PE2 HOUSING WITHOUT CARRIER (SURFACE MOUNT)



PLANAR MONOLITHICS INDUSTRIES, INC

7311-F GROVE ROAD FREDERICK, MARYLAND 21704 USA TEL: 301-662-5019 FAX: 301-662-1731 WEBSITE: www.pmi-rf.com E-MAIL: sales@pmi-rf.com

ISO 9001 CERTIFIED



		TITLE								
APPROVALS DATE			PRODUCT FEATURE							
DRAWN 12/2/14			PE2-15-4G18G-4R0-24-12-SFF-HIP							
CHECKED		SIZE	FSCM NO.		DWG NO.				REV.	
IOOUED.		A 05X		XQ0	PRELIMINARY			1		
ISSUED		SCALE	N·S				SHEET	1 OF	1	