

Description:

Model Number PEC-30-100M500M-2R5-15-12-SFF is a 100 - 500 MHz low noise amplifier that has a gain of 30dB and a Noise Figure of 2.5dB. The OP1dB is >15dBm and the OIP3 is >30dBm.

This model provides the following performance.

Specifications:

Frequency Range: 100 to 500 MHz
 Gain: 25dB Minimum
 Gain Flatness: +/- 3.0 dB Maximum
 Noise Figure: 2.0 dB Typical, 2.5dB Maximum
 P1dB: +15 dBm Minimum
 OIP3: +30 dBm Minimum
 Input Power Handling: +17 dBm CW Maximum
 VSWR Input/Output: 1.5:1 / 2.0:1 Typical
 DC Voltage Supply: +15VDC
 DC Current Draw: 200mA Nominal
 Finish: Blue Epoxy Paint
 Bottom Gold Plated (Unpainted)

Environmental Ratings:


Temperature: -55°C to +85° C (Operating)
 -65°C +117°C (Storage)
 Humidity: MIL-STD-202F, METHOD 103B COND B.
 Shock: MIL-STD-202F, METHOD 213B COND B.
 Altitude: MIL-STD-202F, METHOD 105C COND B.
 Temperature Cycle: MIL-STD-202F, METHOD 107D COND A

Note: The above specifications are subject to change or revision.

ALL DIMENSIONS ARE IN INCHES
 TOLERANCES:
 X.XX ±0.020
 X.XXX ±0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY (-QF)	12/9/14	

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
 FREDERICK, MARYLAND 21704 USA
 TEL: 301-662-5019 FAX: 301-662-1731
 WEBSITE: www.pmi-rf.com
 E-MAIL: sales@pmi-rf.com
 ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE		
DRAWN <i>K. MASON</i>		12/9/14	PRODUCT FEATURE		
CHECKED			PEC-30-100M500M-2R5-15-12-SFF		
ISSUED			SIZE A	FSCM NO. 05XQ0	DWG NO. PRELIMINARY
			SCALE N:S	SHEET 1 OF 1	