

DESCRIPTION

PMI MODEL NO. P2T-0R8G3G-60-R-TNC-200W IS A SINGLE POLE, TWO THROW, REFLECTIVE SWITCH THAT OPERATES OVER THE FREQUENCY RANGE OF 0.8 TO 3.0 GHz. IT HAS A TYPICAL INSERTION LOSS OF 1.5 dB AND A MINIMUM ISOLATION OF 60 dB. THIS MODEL IS OUTFITTED WITH TNC FEMALE CONNECTORS AND A 9-PIN D FEMALE CONNECTOR.

SPECIFICATIONS

- FREQUENCY RANGE: 0.8 TO 3.0 GHz
- INSERTION LOSS: 1.5 dB TYP
- ISOLATION: 60 dB MIN
- VSWR: 2.0:1
- POWER HANDLING: 200 WATTS CW
- SWITCHING SPEED: 1 μ s TYP
- POWER SUPPLY: +5 V @ 450 mA
-48 V / -70 V @ 100 mA
- CONTROL: TTL
"1" = J1-J2 LOW LOSS
"0" = J1-J3 LOW LOSS
- RF CONNECTORS: TNC FEMALE
- CONTROL CONNECTOR: 9-PIN D FEMALE
- SIZE: 3.00" x 2.00" x 0.75"
- FINISH: PAINTED BLUE
(NO PAINT ON MOUNTING SURFACE)
- DC/CTL CONNECTIONS:

DC/CTL	CONNECT TO
1	-48 / -70V
2	GROUND
3	CONTROL
4	+5V
5	NC
6	GROUND
7	GROUND
8	GROUND
9	GROUND

ENVIRONMENTAL RATINGS

- TEMPERATURE: -40°C TO +85°C
- ENVIRONMENTAL: MIL-STD-810E
- EMI/EMC: MIL-STD-461


NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

ALL DIMENSIONS
ARE IN INCHES [mm]
TOLERANCES:
X.XX \pm 0.020
X.XXX \pm 0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	2/12/2019	

MECHANICAL OUTLINE



PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD

FREDERICK, MARYLAND 21704 USA

TEL: (301)-662-5019, FAX: (301)-662-1731

WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com

ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE	
DRAWN		2/12/10		PRODUCT FEATURE	
REDRAWN				P2T-0R8G3G-60-R-TNC-200W	
ISSUED				SP2T REFLECTIVE SWITCH	
SIZE	A	FSCM NO.	05XQ0	DWG NO.	PRELIMINARY
SCALE	N:S			SHEET	1 OF 1