


DESCRIPTION

PMI MODEL: 9CL3130-340-CD-SFF IS A 9 POLE BAND PASS FILTER WITH A CENTER FREQUENCY OF 3130 MHz AND A NOMINAL BANDWIDTH OF 340 MHz.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	12/04/15	

MECHANICAL OUTLINE



SPECIFICATIONS

- CENTER FREQUENCY: ----- 3130 MHz
- PASSBAND FREQUENCY: ----- 2960 TO 3300 MHz
- PASSBAND INSERTION LOSS: ----- 1.5 dB MAXIMUM
- PASSBAND AMPLITUDE FLATNESS: -- 1.0 dB MAXIMUM
- PASSBAND VSWR: ----- 1.5:1 MAXIMUM
- STOP BAND REJECTION: ----- 45 dB @ DC TO 2780 MHz MINIMUM
45 dB @ 3480 TO 6000 MHz MINIMUM
- IMPEDANCE: ----- 50 Ω
- POWER HANDLING: ----- 2 WATTS MAXIMUM
- CONNECTORS: ----- SMA FEMALE
- SURFACE FINISH: ----- BLUE EPOXY POLIMIDE COATING IAW MIL-C-22750, TYPE I OVER EPOXY POLIMIDE PRIMER IAW MIL-P-23377, TYPE I, CLASS 1 OR 3.

ENVIRONMENTAL RATINGS

- TEMPERATURE: ----- -40 °C TO +85 °C (OPERATING)
-55 °C TO +85 °C (STORAGE)
- HUMIDITY: ----- MIL-STD-202F, METHOD 103B COND. B
- SHOCK: ----- MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: ----- MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: ----- MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: ----- MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: (301)-662-5019, FAX: (301)-662-1731
WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE			
DRAWN <i>M. Berry</i>		12/04/15	PRODUCT FEATURE 9CL3130-340-CD-SFF			
CHECKED			SIZE	FSCM NO.	DWG NO.	REV.
ISSUED			A	05XQ0	PRELIMINARY	-
SCALE N:S			SHEET 1 OF 1			