

DESCRIPTION

PMI MODEL PS-400M2000M-360-8D IS A 400 TO 2000 MHz, 8-BIT, VECTOR PHASE SHIFTER MAKING IT IDEAL FOR FREQUENCY TRANSLATION WHERE CONTINUOUS MONOTONIC PHASE SHIFTING IS REQUIRED. THIS MODEL ALSO FEATURES HIGH SPEED SWITCHING, AND TYPICALLY LOWER THAN 50dB HARMONIC DISTORTION.

SPECIFICATIONS

- FREQUENCY RANGE: 400–2000 MHz
- PHASE RANGE: 360 DEGREES
- RF INPUT POWER: +10 dBm CW, 1.0 Watt MAX
- INSERTION LOSS: 13.0 dB MAX
- VSWR: 2.0:1 MAX (50 OHM SYSTEM)
- PHASE VS FREQUENCY: ± 15.0 DEGREES TYP.
- CONTROL LOGIC: 8 BIT TTL COMPATIBLE
- CONTROL SLOPES: LINEAR
- SWITCHING SPEED: 500 nSec MAX
- POWER SUPPLY: ± 12V TO ± 15V @ ±100mA MAX
- RF CONNECTORS: SMA FEMALE INPUT AND OUTPUT
- POWER/LOGIC CONNECTIONS: DC–37P, SUB MINIATURE D MULTI–PIN
- SIZE: 5.0" X 5.0" X 1.0"
- FINISH: PAINTED BLUE

ENVIRONMENTAL RATINGS

- TEMPERATURE RANGE: –10°C TO +60°C (OPERATING)
–65°C TO +125°C (STORAGE)
- HUMIDITY: MIL–STD–202G, METHOD 103B COND. B
- SHOCK: MIL–STD–202G, METHOD 213B COND. B
- VIBRATION: MIL–STD–202G, METHOD 204D COND. B
- ALTITUDE: MIL–STD–202G, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL–STD–202G, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES TOLERANCES: X.XX ±0.020
X.XXX ±0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	–	PRELIMINARY	6-24-14	

37-PIN CONNECTOR PIN-OUT			
PIN	FUNCTION	PIN	FUNCTION
1	1.41 DEG (LSB)	20	NC
2	2.81 DEG	21	5.63 DEG
3	11.25 DEG	22	NC
4	22.5 DEG	23	NC
5	45 DEG	24	NC
6	90 DEG	25	180 DEG (MSB)
7	NC	26	NC
8	+12 TO +15V	27	NC
9	GND	28	GND
10	GND	29	NC
11	–12 TO –15V	30	NC
12	NC	31	NC
13	NC	32	NC
14	NC	33	NC
15	NC	34	NC
16	NC	35	NC
17	NC	36	NC
18	NC	37	NC
19	NC		

PMI CONFIDENTIAL AND PROPRIETARY




PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001:2008 CERTIFIED



APPROVALS		DATE	TITLE			
DRAWN	PJK	6-23-14	PRODUCT FEATURE			
MODIFIED			PS-400M2000M-360-8D			
ISSUED			SIZE	FSCM NO.	DWG NO.	REV.
			A	05XQ0	270XXXXX	–
			SCALE	N:S	SHEET	1 OF 2

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	6-23-14	



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
 FREDERICK, MARYLAND 21704 USA
 TEL: 301-662-5019 FAX: 301-662-1731
 WEBSITE: www.pmi-rf.com
 E-MAIL: sales@pmi-rf.com
 ISO 9001:2008 CERTIFIED



APPROVALS		DATE	TITLE			
DRAWN	PJK	6-23-14	PRODUCT FEATURE			
MODIFIED			PS-400M2000M-360-8D			
ISSUED			SIZE	FSCM NO.	DWG NO.	REV.
			A	05XQ0	270XXXXX	-
			SCALE	N:S	SHEET	2 OF 2

ALL DIMENSIONS ARE IN INCHES TOLERANCES: X.XX ±0.020
 X.XXX ±0.010