# DESCRIPTION

THE MODEL PMI LM-20M18G-100W-15DBM-ROHS IS AN RF LIMITER THAT OPERATES IN THE RANGE OF FREQUENCIES FROM 20MHZ TO 18GHZ. THIS LIMITER CAN HANDLE UP TO 100W CW MORE THAN 20MHZ TO 18GHZ, FOR ALL TEMPERATURES (-55 ° TO +85 ° C) THE ENERGY INPUT PROVIDES LEAKS OF + 15DBM MAX. THIS MODEL HAS A LOW INSERTION LOSS OF 2.60 dB AND A MAXIMUN 100NSEC RECOVERY TIME.

	REVISIONS			
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	03/14/23	

# **SPECIFICATIONS**

FREQUENCY RANGE: --- 20 MHz TO 18.0 GHz

RF POWER HANDLING:--- 100W CW MAX. @ -55 °C TO +85°C

1KW PEAK MIN. +85°C (1µs Pulse Width, 0.1% Duty Cycle)

100W (1µs, 1% DUTY CYCLE, 10KHZ) 100W (10 us. 0.1% DUTY CYCLE, 100HZ) 100W (1 µs, 0.1% DUTY CYCLE, 1KHZ) 100W (40 µs, 10% DUTY CYCLE, 2.5KHZ)

INSERTION LOSS: ----- 2.60 dB MAX. @ -10 dBm INPUT POWER

RECOVERY TIME:---- 100 ns MAX. @ 100 W PEAK POWER

LEAKAGE POWER: ---- +15 dBm MAX. AT 100W CW

VSWR: ----- 2.0:1 MAX. @ -10 dBm INPUT POWER

LIMITING THRESHOLD: (P1dB)----

+5 dBm MINIMUM CONNECTORS: ---- INPUT: SMA MALE

**OUTPUT: SMA FEMALE** 

WEIGHT: ----- 20g [0.705 oz] MAX.

(L) 22.86mm x (W) 9.65mm x (H) 9.65mm MAX.

[(L) 0.90" x (W) 0.38" x (H) 0.38" MAX. **EXCLUDING CONNECTORS** 

FINISH: ---- PAINTED BLUE

### 39.14 [1.54] GOAL 41.66 [1.64] MAX 9.65 9.53 22.86 6.73 [0.38][0.90] [0.38][0.27]**TYP** PLANAR MONOLITHICS 05XQ0 20 MHz TO 18.0 GHz COAXIAL LIMITER MODEL NO: LM-20M18G-100W-15DBM-ROHS SERIAL NO: PLXXXXX/XXXX 4.83 [0.19]

# **ENVIRONMENTAL RATINGS**

#### IAW MIL-E-5400, CLASS 2 EQUIPMENT

• TEMPERATURE: ----- -55 °C TO +85 °C (OPERATING)

-62 °C TO +95 °C (STORAGE)

• VIBRATION: ---- 0.1 inchpp OR ± 10G, 5 ~ 500 Hz (FIGURE 2, SHEET 1 OF 3, CURVE IV)

• SHOCK: ----- 15G, 11±1 ms

• HUMIDITY: ----- 100%

• ALTITUDE: ---- 70.000 FT

7309-A GROVE ROAD FREDERICK, MARYLAND 21704 USA TEL: (301)-662-5019, FAX: (301)-662-1731 WEB: www.pmj-rf.com, EMAIL: sales@pmj-rf.com ISO 9001 CERTIFIED TITLE **OUTLINE** APPROVALS DATE LM-20M18G-100W-15DBM-ROHS DRAWN 03/14/23 MDL REDRAWN SIZE FSCM NO. DWG NO. 27046140 A1 Α 05XQ0

SCALE N:S

**TYP** 

SHEET

1 OF 1

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

**PMI CONFIDENTIAL AND PROPRIETARY**