## **DESCRIPTION**

PMI MODEL: LM-300M1G-21-360W-SFF IS A HIGH POWER LIMITER OPERATING IN THE FREQUENCY RANGE 300 MHz TO 1.0 GHz, WITH 250W OF CW POWER HANDLING (+54 dBm), AND 360W PEAK. THIS COMPACT HOUSING IS FITTED WITH SMA FEMALE CONNECTORS.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	03/10/20	

## **SPECIFICATIONS**


• FREQUENCY RANGE 300 MHz to 1.0 GHz

 POWER HANDLING +54 dBm CW Max, (250Watts),

Peak Power 360W, Pulse 2ms, 10% Duty Cycle

 VSWR (IN/OUT) 2:1 Max. • FLAT LEAKAGE POWER +21 dBm Typ. RECOVERY TIME 1 µs Max. • CONNECTORS **SMA FEMALE**  PACKAGE SIZE 1.00" x 0.68" x 0.35"

 PACKAGE FINISH **BLUE PAINT** 



## **ENVIRONMENTAL RATINGS**

• TEMPERATURE: ----- -40 °C TO +85 °C (OPERATING) -55 °C TO +125 °C (STORAGE) • HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B • SHOCK: ----- MIL-STD-202, METHOD 213B COND. B • VIBRATION; ------ MIL-STD-202, METHOD 204D COND, B • ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B • TEMPERATURE CYCLE: ----- MIL-STD-202, METHOD 107D COND. A

## PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD FREDERICK, MARYLAND 21704 USA TEL: (301)-662-5019, FAX: (301)-662-1731

WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com



PMI CONFIDENTIAL AND PROPRIETARY

CHECKED

ISSUED

ESCM NO **A1** Α 05XQ0 27034606 SCALE N:S SHEET 1 OF 1