

DESCRIPTION

THE MODEL P8T-500M18G-60-T-SFF-JW IS A HIGH SPEED, SINGLE POLE, EIGHT THROW, ABSORPTIVE SWITCH CAPABLE OF SWITCHING WITHIN 100nsec. THE FREQUENCY RANGE IS 0.5 TO 18.0 GHz AND THIS SWITCH HAS OVER 60dB OF ISOLATION.

SPECIFICATIONS

- FREQUENCY RANGE:.....0.5 TO 18.0 GHz
- ISOLATION:.....60dB MIN
- INSERTION LOSS:.....4.5dB MAX
- VSWR IN/OUT:.....2.0:1 MAX
- OPERATING INPUT POWER:.....+20dBm CW
- SWITCHING SPEED:.....100ns MAX
- DC VOLTAGE AND CURRENT:.....+5VDC @ 400mA
-5VDC @ 100mA
- CONTROL SIGNAL:.....EIGHT LINE TTL
 - E1 CONTROLS J1-J2
 - E2 CONTROLS J1-J3
 - E3 CONTROLS J1-J4
 - E4 CONTROLS J1-J5
 - E5 CONTROLS J1-J6
 - E6 CONTROLS J1-J7
 - E7 CONTROLS J1-J8
 - E8 CONTROLS J1-J9
 - "0" ISOLATION
 - "1" INSERTION LOSS
- CONNECTORS:.....SMA (F)
- FINISH:.....GOLD PLATED
- SIZE:.....4.0" X 1.5" X 0.4"


ENVIRONMENTAL RATINGS

- TEMPERATURE:.....-55°C TO +95°C (OPERATING)
-65°C TO +120°C (STORAGE)
- HUMIDITY:.....MIL-STD-202F, METHOD 103B COND. B
- SHOCK:.....MIL-STD-202F, METHOD 213B COND. B
- VIBRATION:.....MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE:.....MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE:.....MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010
WEIGHT: 2.75 oz.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	12/09/11	
	A2	ECN # 13-0128	8/27/13	



PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001:2008 CERTIFIED



APPROVALS		DATE		TITLE	
DRAWN		12/09/11		PRODUCT FEATURE	
CHECKED				P8T-500M18G-60-T-SFF-JW	
ISSUED				0.5 TO 18.0 GHz HIGH SPEED SWITCH 8 THROW	
SIZE		FSCM NO.		DWG NO.	
A		05XQ0		27015887	
SCALE		N:S		SHEET	
				1 OF 1	