


DESCRIPTION

PMI MODEL APD-2-100M20G-CD-1 IS A TWO WAY POWER DIVIDER FEATURING HIGH ISOLATION, LOW INSERTION LOSS, AND LOW VSWR. IT IS DESIGNED FOR BROADBAND USE AND HIGH RELIABILITY.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	7/28/17	



SPECIFICATIONS

- FREQUENCY RANGE: 0.1 TO 20 GHz
- INSERTION LOSS: 0.1 TO 8.0 GHz, 1.85dB TYPICAL
8.0 TO 20 GHz, 3.5dB TYPICAL
- VSWR: 0.1 TO 0.5 GHz, 2.0:1 TYPICAL
0.5 TO 8.0 GHz, 1.5:1 TYPICAL
8.0 TO 20 GHz, 1.6:1 TYPICAL
- ISOLATION: 0.1 TO 0.5 GHz, 6dB TYPICAL
0.5 TO 8.0 GHz, 16.5dB TYPICAL
8.0 TO 20 GHz, 21.0dB TYPICAL
- AMPLITUDE BALANCE: 0.1 TO 8.0 GHz, ±0.2dB TYPICAL
8.0 TO 20 GHz, ±0.45dB TYPICAL
- PHASE BALANCE: 0.1 TO 8.0 GHz, ±4° TYPICAL
8.0 TO 20 GHz, ±5° TYPICAL
- AVERAGE POWER INTO LOAD VSWR:
1.2:1 25 WATTS
2.0:1 7.5 WATTS
∞:1 0.75 WATTS
- SIZE: 3.75" (L) x 1.00" (W) x 0.40" (H)
- FINISH: GOLD PLATED

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ENVIRONMENTAL RATINGS:

- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE		
DRAWN <i>JPH</i>		7/28/17	PRODUCT FEATURE APD-2-100M20G-CD-1 0.1 - 20 GHz 2 WAY POWER DIVIDER		
CHECKED			SIZE A	FSCM NO. 05XQ0	DWG NO. PRELIMINARY
ISSUED			SCALE N:S		SHEET 1 OF 1

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010