DESCRIPTION

LOW NOISE AMPLIFIER DESIGNED FOR MILITARY AND INDUSTRIAL APPLICATIONS. THIS AMPLIFIER IS SUPPLIED IN OUR STANDARD PE2 HOUSING THAT CAN BE USED AS AN SMA CONNECTORIZED OR A SURFACE MOUNT COMPONENT. OTHER PACKAGES AND CONNECTOR TYPES ARE AVAILABLE. THIS MODEL PROVIDES THE FOLLOWING PERFORMANCE. DATA IS AVAILABLE UPON REQUEST.

SPECIFICATIONS

	FREQUENCY	RANGE:	 Lι	1	to	8.0	GH7
•	INCUDENCI	IVAINGE.	 ۲.۱	J	LO.	0.0	GIIZ

• GAIN:	45dB	MINIMUM.	55dB	MAXIMUM
---------	------	----------	------	---------

• GAIN FLATNESS: ±1.5dB MAXIMUM

NOISE FIGURE:
 3dB GOAL, 3.5dB MAXIMUM

EXCLUDING CONNECTORS

• FINISH — GOLD PLATED

FEATURES

- INTERNAL VOLTAGE REGULATION
- UNCONDITIONAL STABILITY

AVAILABLE OPTIONS

- VARIOUS PACKAGE TYPES
- VARIOUS CONNECTOR TYPES
- TEMPERATURE COMPENSATION
- GAIN AND PHASE MATCHING
- MIL-STD-883 SCREENING AVAILABLE

ENVIRONMENTAL RATINGS

- ◆ TEMPERATURE: -54°C TO + 85°C (OPERATING) -65°C TO +125°C (STORAGE)
- HUMIDITY: _____ MIL-STD-202F, METHOD 103B COND. B
- SHOCK: _____ MIL-STD-202F, METHOD 213B COND. B
- ALTITUDE: _____ MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES

TOLERANCES:


X.XX ±0.020

X.XXX ±0.010


REVISIONS								
ZONE	REV.	DESCRIPTION	DATE	APPROVED				
	_	PRELIMINARY	10/4/18					
	1	UPDATED SPECS	10/5/18					

MECHANICAL OUTLINE

PE2 HOUSING WITH CARRIER



PE2 HOUSING WITHOUT CARRIER (SURFACE MOUNT)



PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD FREDERICK, MARYLAND 21704 USA TEL: 301-662-5019 FAX: 301-662-1731 WEBSITE: www.pmi-rf.com E-MAIL: sales@pmi-rf.com ISO 9001 CERTIFIED



APPROVALS	DATE	PRODUCT FEATURE						
DRAWN \mathcal{KM}	8/1/14	PE2-55-4G8G-3R5-22-12-SFF						
REDRAWN &W	10/4/18	SIZE FSCM NO. A 05XQ0			DWG NO. PRELIM	INARY		REV.
ISSUED		SCALE	N:S			SHEET	1 OF	1