
DESCRIPTION:


PFC model number SSBP12G-12G-CD-SFF is a Suspended Substrate filter with SMA female connectors in and out. All filters will be machined and silver plated to provide the highest possible Q.

REVISIONS											
ZONE	REV.	DESCRIPTION	DATE	APPROVED							
	-	ORIGINAL RELEASE	3/13/02								
	Α	UPDATED SPECS	3/21/02								

SPECIFICATIONS:

- CENTER FREQUENCY: 12000 MHz
- 1dB BANDWIDTH: 12000 MHz
- VSWR IN THE PASS BAND: 2.0:1 MAX.
- INSERTION LOSS (PASSBAND) <= -0.5 dB MAX.
- REJECTION @ 8 GHz: -40 dB
- REJECTION @ 20 GHz: -60 dB





- CONNECTORS: SMA FEMALE CONNECTORS
- SIZE 2.1" (L) x 0.785" (W) x 0.50" (H)
- WEIGHT 1 OZ. TYP.



ENVIRONMENTAL RATINGS:

• TEMPERATURE: -55°C TO +85°C (OPERATING) -65°C TO +125°C (STORAGE)

• HUMIDITY: MIL-STD-202F, METHOD 103B COND. B

SHOCK: MIL-STD-202F, METHOD 213B COND. B

• VIBRATION: MIL-STD-202F, METHOD 204D COND. B

ALTITUDE: MIL-STD-202F, METHOD 105C COND. B

SALT FOG: MIL-STD-202F, METHOD 107D COND. A

• FUNGUS: MIL-STD-810C, METHOD 508.2

• TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

ALL DIMENSIONS ARE IN INCHES TOLERANCES: X.XX ±0.010 X.XXX ±0.005

PART NO. 155-1164	Planar Filter Company 7311G Grove Road, Fredrick, Maryland							
APPROVALS	DATE	TITLE		31040	1000,110	Janok, Wi	ai yiai ia	
S. PALACIO	3/13/02	OUTLINE DRAWING SSBP12G-12G-CD-SFF						
CHECKED F. HOYOS	3/21/02	0001120 120 00 011						
ISSUED		SIZE	FSCM NO.		DWG NO.			REV.
		Α	1Q	JWO		155 - 1	164	A
		SCALE	N/A				SHEET 1 OF	1

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION