

DESCRIPTION

PMI MODEL NO. LM-400M4G-20CW-220WP-SFF-PE2 IS A HIGH POWER LIMITER THAT WORKS FROM 400 MHz TO 4000 MHz AND HANDLES INPUT POWER LEVELS OF 20 W CW AND 220 W PEAK, 10% DUTY CYCLE, 1 USEC PULSE WIDTH.

SPECIFICATIONS

- FREQUENCY RANGE: _____ 400 TO 4000 MHz
- INSERTION LOSS: _____ 1.2 dB TYPICAL
- MAX PEAK POWER: _____ 220 WATTS, 10% DUTY CYCLE, 1 USEC PW
- MAX AVERAGE POWER: _____ 20 WATTS CW
- LEAKAGE POWER: _____ +13 dBm TYPICAL
- RECOVERY TIME: _____ 10 ns TYPICAL
- VSWR: _____ 1.5:1 TYPICAL
- DC BLOCKING: _____ INPUT AND OUTPUT
- CONNECTORS: _____ SMA FEMALE REMOVABLE
- SIZE: _____ 1.08" x 0.71" x 0.29"
EXCLUDING CONNECTORS
- FINISH: _____ GOLD PLATED

ENVIRONMENTAL RATINGS


- TEMPERATURE: _____ -40°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: _____ MIL-STD-202F, METHOD 103B COND. B
- SHOCK: _____ MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: _____ MIL-STD-202F, METHOD 204B COND. B
- ALTITUDE: _____ MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: _____ MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	7/2/18	

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE			
DRAWN <i>EW</i>		7/2/18	PRODUCT FEATURE			
CHECKED			LM-400M4G-20CW-220WP-SFF-PE2			
ISSUED			SIZE	FCSM NO.	DWG NO.	REV.
			A	05XQ0	PRELIMINARY	-
			SCALE	N:S	SHEET	1 OF 1