


DESCRIPTION:

PFC model number BP750-300-3B-SS is a LC Bandpass filter with SMA connectors in and out. All filters will be machined and silver plated to provide the highest possible Q.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	ORIGINAL RELEASE	6/15/00	

SPECIFICATIONS:

- CENTER FREQUENCY: 750 MHz
- 1dB BANDWIDTH: 300 MHz
- VSWR IN THE PASS BAND: 1.5:1 MAX.
- INSERTION LOSS (PASSBAND) : -1.5 dB MAX.
- REJECTION FROM DC TO 450 MHz: -60 dB MIN.
- REJECTION FROM 1050 TO 5000 MHz: -60 dB



- INPUT & OUTPUT : SMA CONNECTORS
- SIZE : 1.50" (L) x 0.50" (W) x 0.50" (H)
- WEIGHT : 1 OZ. TYP.

ENVIRONMENTAL RATINGS:

- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- SALT FOG: MIL-STD-202F, METHOD 107D COND. A
- FUNGUS: MIL-STD-810C, METHOD 508.2
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
XXX ±0.010
XXX ±0.005

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PART NO. PF60-168		Planar Filter Company 7311G Grove Road, Fredrick, Maryland	
APPROVALS	DATE	TITLE	
S. PALACIO	6/15/00	OUTLINE DRAWING BP750-300-3B-SS	
CHECKED		SIZE	FSCM NO.
		A	OZXZ8
ISSUED		DWG NO.	REV.
		155-0222	-
SCALE N/A		SHEET 1 OF 1	