# **DESCRIPTION**

PMI MODEL NO. P2T-30M6-70-T-SFF IS A SINGLE POLE, TWO THROW, ABSORPTIVE SWITCH THAT OPERATES OVER THE FREQUENCY RANGE OF 30 MHz TO 6.0 GHz, IT HAS A MINIMUM ISOLATION OF 70 dB AND A MINIMUM RETURN LOSS OF -12 dB. THIS MODEL IS OUTFITTED WITH SMA FEMALE CONNECTORS.

PEAK 8 WATTS MAX @ 1 us

| REVISIONS |      |             |            |          |
|-----------|------|-------------|------------|----------|
| ZONE      | REV. | DESCRIPTION | DATE       | APPROVED |
|           | -    | PRELIMINARY | 11/19/2019 |          |
|           |      |             |            |          |
|           |      |             |            |          |


### **SPECIFICATIONS**




- ----- 70 dB MIN ISOLATION: ----
- INSERTION LOSS: ------ 2.6 dB MAX
- RETURN LOSS (ALL PORTS ON OR OFF STATE): ----- -12 dB MIN
- RISE/FALL TIME (10% TO 90% RF, 90% TO 10% RF): ----- 80 ns MAX
- ON/OFF TIME (50% TTL TO 90% RF,

- REFLECTED) • POWER SUPPLY: ----- +5 V ± 0,25 V @ 50 mA MAX
- -15 V ± 0.25 V @ 50 mA MAX
- CONTROL LOGIC: ----- 1 BCD, 0 V < "0" < 0.8 V, 2.4 V < "1" < 5 V
- IMPEDANCE: ----- 50 OHMS
- CONNECTORS: ----- SMA FEMALE
- FINISH: ------- ALODINE AND LASER SEALING

# **MECHANICAL OUTLINE**



0.787 [20.00]



#### TRUTH TABLE CE OFF ON J0-J1, J2 1 0 J0-J1 J0-J2 1 0 J0-J2 J0-J1

### **ENVIRONMENTAL RATINGS**

- - -65 °C TO +125 °C (STORAGE)
- HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B
- SHOCK: ----- MIL-STD-202, METHOD 213B COND. B
- VIBRATION: ---- MIL-STD-202, METHOD 204D COND. B
- ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE: ------ MIL-STD-202. METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

**PMI CONFIDENTIAL AND PROPRIETARY** 

ALL DIMENSIONS ARE IN INCHES [mm]

TOLERANCES:

±0.020

ISSUED

X.XX

X.XXX

# PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD

FREDERICK, MARYLAND 21704 USA TEL; (301)-662-5019, FAX; (301)-662-1731

WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com ISO 9001 CERTIFIED

TITLE APPROVALS 11/19/19 EW REDRAWN

PRODUCT FEATURE P2T-30M6-70-T-SFF

0.315 [8.00]

SIZE FSCM NO. Α 05XQ0 **PRELIMINARY** 

SCALE N:S SHEET 1 OF 1