## **DESCRIPTION:**

PFC model number LP2D5G-2D7G-CD-SMF is a LC Lowpass filter with SMA female connectors in and out.

	REVISIONS											
ZONE	REV.	DESCRIPTION	DATE	APPROVED								
	-	ORIGINAL RELEASE	8/11/00									

## **SPECIFICATIONS:**

PASSBAND:
 1 MHz TO 2.5 GHz


• 3dB BANDWIDTH: 2.7 GHz


• VSWR IN THE PASS BAND: 1.5:1 MAX.

• INSERTION LOSS (PASSBAND) <-1 dB MAX.

● REJECTION AT 5 GHz: -50 dB MIN.

● REJECTION AT 5 GHz TO 15 GHz: -40 dB






• CONNECTORS: SMA FEMALE CONNECTORS

• SIZE 0.75" (L) x 0.31" (W) x 0.31" (H)

WEIGHT
 1 OZ. TYP.



## **ENVIRONMENTAL RATINGS:**

TEMPERATURE: -55°C TO +85°C (OPERATING)

-65°C TO +125°C (STORAGE)

HUMIDITY: MIL-STD-202F, METHOD 103B COND. B SHOCK: MIL-STD-202F, METHOD 213B COND. B VIBRATION: MIL-STD-202F, METHOD 204D COND. B

TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

ALL DIMENSIONS ARE IN INCHES TOLERANCES: X.XX ±0.010 X.XXX ±0.005

PF60-29	Planar Filter Company 7311G Grove Road, Fredrick, Maryland								
APPROVALS	DATE	TITLE	3110 010	310 .	1000, 110	diloit, ivi	ai yiai k		
S PALACIO	8/11/00	OUTLINE DRAWING LP2D5G-2D7G-CD-SMF							
CHECKED		LF ZDJG-ZD/G-CD-JMF						I	
ISSUED		SIZE	FSCM NO.		DWG NO.				REV.
		Α	4   1QJWO		155-0374				-
		SCALE	N/A				SHEET	1 OF	1