

DESCRIPTION

LOW NOISE AMPLIFIER DESIGNED FOR MILITARY AND INDUSTRIAL APPLICATIONS. THIS AMPLIFIER IS SUPPLIED IN OUR STANDARD PE2 HOUSING THAT CAN BE USED AS AN SMA CONNECTORIZED OR A SURFACE MOUNT COMPONENT. OTHER PACKAGES AND CONNECTOR TYPES ARE AVAILABLE. THIS MODEL PROVIDES THE FOLLOWING PERFORMANCE. DATA IS AVAILABLE UPON REQUEST.

SPECIFICATIONS

- FREQUENCY RANGE: _____ 1.0 TO 13.0 GHZ
- GAIN: _____ 35 dB MINIMUM
- GAIN FLATNESS: _____ ± 1.5 dB MAXIMUM
- NOISE FIGURE: _____ 2.5 dB MAXIMUM @ 25 °C
- OP1dB: _____ 12 dBm MINIMUM
- VSWR (IN/OUT): _____ 2.0:1 MAXIMUM
- CONNECTORS: _____ SMA (F) REMOVABLE
- DC SUPPLY: _____ +12 VDC @ 250 mA MAXIMUM
- SIZE _____ (L) 1.08" X (W) 0.71" X (H) 0.29"
EXCLUDING CONNECTORS
- FINISH _____ GOLD PLATED

FEATURES

- INTERNAL VOLTAGE REGULATION
- UNCONDITIONAL STABILITY
- STANDARD OPERATING TEMPERATURE
-20 TO +70 DEG. C

AVAILABLE OPTIONS

- VARIOUS PACKAGE TYPES
- VARIOUS CONNECTOR TYPES
- TEMPERATURE COMPENSATION
- HERMETIC SEALING
- GAIN AND PHASE MATCHING
- MIL-STD-883 SCREENING AVAILABLE

ENVIRONMENTAL RATINGS


- TEMPERATURE: _____ -20°C TO + 70°C (OPERATING); -55 TO +85 DEG C AVAILABLE
-65°C TO +125°C (STORAGE)
- HUMIDITY: _____ MIL-STD-202F, METHOD 103B COND. B
- SHOCK: _____ MIL-STD-202F, METHOD 213B COND. B
- ALTITUDE: _____ MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: _____ MIL-STD-202F, METHOD 107D COND. A

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ± 0.020
X.XXX ± 0.010

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	1	ORIGINAL RELEASE	6/15/12	

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE			
DRAWN <i>K. MASON</i>		6/15/12	PRODUCT FEATURE			
CHECKED			PE2-35-1G13G-2R5-10-12-SFF			
ISSUED			SIZE A	FSCM NO. 05XQ0	DWG NO. PRELIMINARY	REV. 1
SCALE N:S			SHEET 1 OF 1			