

DESCRIPTION


PMI MODEL NO. BPF-484R5M-10M-PIN IS A BAND PASS FILTER WITH A CENTER FREQUENCY OF 484.5 MHz. IT HAS A MAXIMUM INSERTION LOSS OF 3.48 dB AND A MAXIMUM VSWR OF 1.5:1. THIS MODEL IS OUTFITTED WITH PINS.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	12/21/2018	

MECHANICAL OUTLINE

SPECIFICATIONS

- FREQUENCY RANGE (-3 dB BANDWIDTH): — 479.5 TO 489.5 MHz
- INSERTION LOSS @ 484.5 MHz: — 3.48 dB MAX
- PASS BAND RIPPLE: — ±0.5 dB MAX
- VSWR: — 1.5:1 MAX
- REJECTION @ 516 MHz: — 40 dBc MIN
- INPUT POWER: — 1 WATT MAX
- IMPEDANCE: — 50 OHMS
- CONNECTORS: — PIN



ENVIRONMENTAL RATINGS

- TEMPERATURE: — -20 °C TO +70 °C (OPERATING)
— -65 °C TO +125 °C (STORAGE)
- HUMIDITY: — MIL-STD-202, METHOD 103B COND. B
- SHOCK: — MIL-STD-202, METHOD 213B COND. B
- VIBRATION: — MIL-STD-202, METHOD 204D COND. B
- ALTITUDE: — MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE: — MIL-STD-202, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

ALL DIMENSIONS
ARE IN INCHES [mm]
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD

FREDERICK, MARYLAND 21704 USA

TEL: (301)-662-5019, FAX: (301)-662-1731

WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com

ISO 9001 CERTIFIED



		TITLE PRODUCT FEATURE BPF-484R5M-10M-PIN									
APPROVALS								DATE			
DRAWN <i>EW</i>								12/21/18			
REDRAWN				SIZE A	FSCM NO. 05XQ0	DWG NO. PRELIMINARY	REV. -				
ISSUED				SCALE N:S		SHEET 1 OF 1					