

DESCRIPTION

PMI MODEL TD-30T-SHS-218 IS A HIGH SPEED, TTL LOGIC OUTPUT THRESHOLD DETECTOR DESIGNED TO OPERATE FROM 2.0 GHz TO 18.0 GHz. THIS DETECTOR HAS A PROPAGATION DELAY OF 15 ns MAXIMUM.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	12/2/08	
	A2	ECN # 13-0055	06/03/13	


SPECIFICATIONS

- FREQUENCY RANGE: 2 GHz TO 18 GHz
- VSWR: 3.0 : 1 MAXIMUM @ -20 dBm
- MINIMUM SIGNAL LEVEL FOR LOGIC 1: -20 dBm @ 2 GHz
-17 dBm @ 18 GHz
- THRESHOLD VARIATION OVER FREQUENCY (ANY 1 GHz WINDOW): ±0.5 dB
- MINIMUM SIGNAL LEVEL FOR LOGIC 0: -25 dBm
- DYNAMIC RANGE: UP TO +10 dBm
- PROPAGATION DELAY (FROM 50% OF AN INPUT OF -20 dBm): 15 ns MAX
- PROPAGATION DELAY (FROM 50% OF AN INPUT OF +10 dBm): 15 ns MAX
- DC POWER SUPPLY
 - +V: +15 VOLTS @ 100 mA MAX
 - V: -15 VOLTS @ 100 mA MAX
- SIZE: 2.2" x 1.50" x 0.40"
- WEIGHT: < 3 OUNCES
- FINISH: GOLD PLATED

ENVIRONMENTAL RATINGS

- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +100°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE		
DRAWN <i>DPD</i>		12/2/08	PRODUCT FEATURE TD-30T-SHS-218		
REDRAWN			SIZE	FSCM NO.	DWG NO.
ISSUED			A	05XQ0	27009521
			SCALE	N:S	SHEET 1 OF 1
			REV.	A2	

NOTES:

- 1) DIMENSIONS ARE IN INCHES
- 2) TOLERANCES: X.XX ±0.020
X.XXX ±0.010
- 3) WEIGHT: 2.75 OZ