



**SUMMARY TEST DATA
ON
PEC4-16-8G18G-4R7-18-15-SFF-OPTSL**

Customer: _____ Tested By: FREDESWINDO C. CORTES JR
SO No: _____ Temperature: +25°C
Model No: PEC4-16-8G18G-4R7-18-15-SFF-OPTSL Date: 08/06/24
Serial No: PL47477/2432 Drawing No: 27628833 Rev: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	8.0 to 18.0 GHz	8.0 to 18.0 GHz	PMI QA3
2	Gain @ 8.0 GHz:	13 dB Min, 16 dB Max	15.97dB (See Plot)	
3	Gain Flatness:	±1.50 dB Max	.945dB (See Plot)	
4	Gain Slope to 18.0 GHz:	-2.5 dB to -3.5 dB	1.89dB (See Plot)	
5	Noise Figure:	4.7 dB Max	3.077dB (See Plot)	
6	OP1dB:	+18 dBm Typ	20.09dBm (See Plot)	
7	VSWR Input:	1.67:1 Max	1.45:1 (See Plot)	
8	VSWR Output:	2.25:1 Max	1.74:1 (See Plot)	
9	Maximum Input:	+30 dBm CW	Pass	
10	DC Supply:	+12.5 to +28 VDC @ 250 mA Typ	117mA	

QA/QC Approval:

K. L. [Signature]

Date:


8-8-24

4921 Robert J. Mathews Parkway, Suite 1, El Dorado Hills, CA, 95762
Phone: (916) 542-1401 Fax: (916) 265-2597
Email: sales@pmi-rf.com



**SUMMARY TEST DATA
ON
PEC4-16-8G18G-4R7-18-15-SFF-OPTSL**

GAIN & VSWR




4921 Robert J. Mathews Parkway, Suite 1, El Dorado Hills, CA, 95762
Phone: (916) 542-1401 Fax: (916) 265-2597
Email: sales@pmi-rf.com



**SUMMARY TEST DATA
ON
PEC4-16-8G18G-4R7-18-15-SFF-OPTSL**

NOISE FIGURE





**SUMMARY TEST DATA
ON
PEC4-16-8G18G-4R7-18-15-SFF-OPTSL**

P-1dB

