



Summary Data
For
ERDLVA-2G18G-65-70MV-70C

Customer: _____
 SO No: _____
 Model No: ERDLVA-2G18G-65-70MV-70C
 Serial No: PL48060/2444

Tested By: Anton L.
 Temperature: -40°C TO +70°C
 Date 10/30/2024
 Drawing No: 27642020 Rev: A1

| TEST ITEM NO | PARAMETERS | SPECIFIED VALUE | TEST RESULTS | QA QC |
|--------------|-----------------------------------|--|--------------------------|--------------------------|
| 1 | Frequency Range: | 2 to 18 GHz | 2 to 18 GHz | PMI QA3 |
| 2 | VSWR: | 2.2:1 MAX @ 50 Ω | 1.81 :1 MAX | |
| 3 | Input Power: | (1) 1 W CW, Max. (2) 100 W Peak @ PW = 1 us & Duty Cycle = 1%, Max. | Pass | |
| 4 | VIDEO OUT TSS: | -71 dBm MAX | - 71.8 dBm | |
| 5 | VIDEO OUT Dynamic Range: | -65 to 0 dBm | -65 to 0 dBm | |
| 6 | VIDEO OUT Log Slope Fixed: | 70 ± 3mV/dB | 70.0 mV/dB 68.8 mV/dB | |
| 7 | VIDEO OUT Log Linearity: | ±1.0 dB MAX @25C | 0.58 dB -0.38 dB | |
| 8 | VIDEO OUT Log Accuracy: | ±2.3 dB MAX @25C | 0.77 dB -0.86 dB | |
| 9 | VIDEO OUT Absolute Log Accuracy: | ±2.9 dB MAX Over Freq & temp | 1.22 dB -1.08 dB | |
| 10 | VIDEO OUT DC Offset: | 0 ±70 mV (RF Input Terminated & DC Power On) @25C | 43 mV | |
| 11 | VIDEO OUT Rise Time (10% to 90%): | 28 ns MAX | 23.3 ns | |
| 12 | VIDEO OUT Fall Time (90% to 10%): | 300 ns MAX | 166.3 ns | |



Summary Data
For
ERDLVA-2G18G-65-70MV-70C

| | | | | |
|----|---|--|------------------|------------|
| 13 | VIDEO OUT Settling Time: | 50 ns With in ± 70 mV of final value @-10 dBm | 23.8 ns | PMI QA3 |
| 14 | VIDEO OUT Recovery Time: | 1 us MAX to within 1 dB of baseline for PW <10us & Power = -10dBm | 0.43 us | |
| 15 | VIDEO OUT Video Frequency Flatness: | ± 2.0 dB MAX @25C | ± 0.77 dB | |
| 16 | VIDEO OUT CW Immunity: | CW Immune Power TSS to -40 dBm | Pass | |
| | | Pulse Peak Amplitude Loss; 2 dB MAX @ -40dBm CW | < 2 dB | |
| | | Baseline shift 200mV @-40dBm CW | < 200 mV | |
| | | CW Immunity Time at CW = -40 dBm, ≤ 4 ms | 1.49 ms | |
| | | CW Recovery Time at CW = -40 dBm, ≤ 20 us | <20 us | |
| 17 | Pulse droop | 1dB Max for 300us pulse at or above -65dBm | <1dB | |
| 18 | VIDEO OUT Pulse Response, input Signal: | 100 ns to 300 us | 100 ns to 300 us | |
| 19 | VIDEO LOAD Impedance: | 75 ± 1 Ω | 75 Ω | |
| 20 | VIDEO driver capability | 100 ft RG11 into 75 ohm load | Pass | |
| 21 | Pulse density capability | 10% duty cycle 100 ns, 70% duty cycle 300 us at peak power -10 dBm with 1 dB variable for pulse amplitude and baseline | Pass | |



Summary Data
For
ERDLVA-2G18G-65-70MV-70C

| | | | | |
|----|---------------------------------------|--|---------------------------------|------------|
| 22 | VIDEO OUT Noise Level (Vp-p): | 160 mV max | 116.8 mV | PMI QAS |
| 23 | VIDEO OUT Propagation Delay: | 50 ns MAX from RF 50% to 10% video (excluding cable) | < 50 ns | |
| 24 | Power Supply | +15 V @ 500 mA MAX -15 V @ 100 mA MAX | +15 V @ 320 mA -15 V @ 80 mA | |
| 25 | Power Supply Ripple From DC to 10 MHz | 100 mV MAX | Pass | |

QA/QC Approval: K. Klamm

Date: 11-1-24



Summary Data For ERDLVA-2G18G-65-70MV-70C

LOG TRANSFER WITH FREQUENCY

TESTED BY: Anton L.
 MODEL: ERDLVA-2G18G-65-70MV-70C
 SERIAL NO: PL48060/2444
 DATE: 10/30/2024



Test Temp: 25 °C
 Video Offset: 43 mV

Frequency

| Frequency | Intercept (mV) | Slope (mV/dB) | -65 | -60 | -55 | -50 | -45 | -40 | -35 | -30 | -25 | -20 | -15 | -10 | -5 | 0 |
|------------------|----------------|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 2000 MHz | 4885 | 69.7 | 347 | 707 | 1048 | 1398 | 1765 | 2082 | 2436 | 2801 | 3131 | 3502 | 3873 | 4191 | 4526 | 4867 |
| | | | -7 | 4 | -3 | -2 | 17 | -15 | -9 | 7 | -11 | 11 | 34 | 3 | -10 | -18 |
| | | | -0.10 | 0.06 | -0.05 | -0.02 | 0.24 | -0.21 | -0.13 | 0.10 | -0.16 | 0.16 | 0.48 | 0.04 | -0.15 | -0.26 |
| | | | 0.16 | 0.33 | 0.22 | 0.25 | 0.51 | 0.06 | 0.14 | 0.38 | 0.12 | 0.44 | 0.77 | 0.33 | 0.14 | 0.03 |
| 6000 MHz | 4895 | 70.0 | 342 | 699 | 1043 | 1391 | 1754 | 2075 | 2441 | 2816 | 3147 | 3506 | 3849 | 4178 | 4534 | 4902 |
| | | | -3 | 4 | -2 | -4 | 9 | -20 | -4 | 21 | 2 | 11 | 4 | -17 | -11 | 7 |
| | | | -0.04 | 0.06 | -0.03 | -0.06 | 0.13 | -0.28 | -0.05 | 0.30 | 0.03 | 0.16 | 0.06 | -0.24 | -0.15 | 0.11 |
| | | | 0.09 | 0.21 | 0.15 | 0.14 | 0.35 | -0.04 | 0.21 | 0.60 | 0.35 | 0.50 | 0.42 | 0.15 | 0.25 | 0.54 |
| 10000 MHz | 4836 | 70.0 | 283 | 634 | 974 | 1336 | 1696 | 2018 | 2384 | 2756 | 3090 | 3448 | 3777 | 4122 | 4476 | 4846 |
| | | | 1 | 9 | 10 | 2 | 12 | -17 | 1 | 21 | 5 | 12 | 9 | -14 | -10 | 18 |
| | | | -0.01 | 0.00 | -0.14 | 0.03 | 0.16 | -0.24 | -0.01 | 0.30 | 0.07 | 0.18 | -0.12 | -0.20 | -0.15 | 0.14 |
| | | | -0.76 | -0.72 | -0.84 | -0.64 | -0.48 | -0.86 | -0.60 | -0.26 | -0.47 | -0.33 | -0.61 | -0.66 | -0.58 | -0.27 |
| 14000 MHz | 4874 | 69.8 | 334 | 693 | 1034 | 1384 | 1732 | 2055 | 2427 | 2800 | 3132 | 3493 | 3829 | 4168 | 4519 | 4873 |
| | | | -2 | 8 | 0 | 1 | -1 | -27 | -4 | 20 | 3 | 15 | 2 | -8 | -6 | -1 |
| | | | -0.03 | 0.11 | -0.01 | 0.01 | -0.01 | -0.38 | -0.05 | 0.29 | 0.05 | 0.22 | 0.03 | -0.11 | -0.09 | -0.02 |
| | | | -0.03 | 0.13 | 0.02 | 0.04 | 0.04 | -0.33 | 0.01 | 0.37 | 0.13 | 0.31 | 0.14 | 0.00 | 0.04 | 0.12 |
| 18000 MHz | 4852 | 68.8 | 373 | 738 | 1081 | 1424 | 1766 | 2077 | 2430 | 2783 | 3116 | 3476 | 3800 | 4149 | 4515 | 4892 |
| | | | -6 | 15 | 14 | 13 | 10 | -23 | -14 | -5 | -16 | 0 | -20 | -15 | 7 | 40 |
| | | | -0.09 | 0.21 | 0.20 | 0.18 | 0.15 | -0.33 | -0.20 | -0.07 | -0.23 | 0.00 | -0.29 | -0.22 | 0.10 | 0.58 |
| | | | 0.53 | 0.77 | 0.70 | 0.62 | 0.53 | -0.01 | 0.06 | 0.12 | -0.10 | 0.07 | -0.28 | -0.27 | -0.02 | 0.39 |

| RF Input Power (dBm) | Measured Value (mV) | Error (mV) | LINEARITY ERROR (dB) | ACCURACY ERROR (dB) |
|----------------------|---------------------|------------|----------------------|---------------------|
| -65 | 347 | -7 | -0.10 | 0.16 |
| -60 | 707 | 4 | 0.06 | 0.33 |
| -55 | 1048 | -3 | -0.05 | 0.22 |
| -50 | 1398 | -2 | -0.02 | 0.25 |
| -45 | 1765 | 17 | 0.24 | 0.51 |
| -40 | 2082 | -15 | -0.21 | 0.06 |
| -35 | 2436 | -9 | -0.13 | 0.14 |
| -30 | 2801 | 7 | 0.10 | 0.38 |
| -25 | 3131 | -11 | -0.16 | 0.12 |
| -20 | 3502 | 11 | 0.16 | 0.44 |
| -15 | 3873 | 34 | 0.48 | 0.77 |
| -10 | 4191 | 3 | 0.04 | 0.33 |
| -5 | 4526 | -10 | -0.15 | 0.14 |
| 0 | 4867 | -18 | -0.26 | 0.03 |

| Flatness | +/- dB | 0.65 | 0.75 | 0.77 | 0.63 | 0.50 | 0.46 | 0.41 | 0.43 | 0.41 | 0.42 | 0.69 | 0.50 | 0.42 | 0.40 |
|----------|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | | | | | | | | | | | | | | | 0.77 |





Summary Data For ERDLVA-2G18G-65-70MV-70C

LOG TRANSFER WITH FREQUENCY

TESTED BY: Anton L.
MODEL: ERDLVA-2G18G-65-70MV-70C
SERIAL NO: PL48060/2444
DATE: 10/30/2024

Test Temp: -40 °C
Video Offset: -57 mV

Frequency

| Frequency | Intercept (mV) | Slope (mV/dB) | -65 | -60 | -55 | -50 | -45 | -40 | -35 | -30 | -25 | -20 | -15 | -10 | -5 | 0 |
|------------------|----------------|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 2000 MHz | 4746 | 70.1 | 202 | 548 | 874 | 1228 | 1599 | 1926 | 2281 | 2650 | 2982 | 3351 | 3728 | 4055 | 4392 | 4725 |
| | | | 13 | 9 | -16 | -12 | 8 | -15 | -11 | 8 | -11 | 7 | 34 | 10 | -3 | -21 |
| | | | 0.19 | 0.13 | -0.22 | -0.17 | 0.12 | -0.22 | -0.16 | 0.11 | -0.16 | 0.11 | 0.48 | 0.15 | -0.05 | -0.30 |
| | | | -0.64 | -0.69 | -1.02 | -0.94 | -0.63 | -0.95 | -0.86 | -0.57 | -0.82 | -0.53 | -0.13 | -0.45 | -0.62 | -0.85 |
| 6000 MHz | 4777 | 70.1 | 238 | 577 | 913 | 1260 | 1626 | 1955 | 2318 | 2695 | 3027 | 3384 | 3737 | 4064 | 4420 | 4780 |
| | | | 16 | 4 | -10 | -13 | 2 | -19 | -6 | 20 | 2 | 9 | 11 | -12 | -6 | 3 |
| | | | 0.22 | 0.06 | -0.14 | -0.19 | 0.03 | -0.27 | -0.09 | 0.29 | 0.03 | 0.12 | 0.16 | -0.17 | -0.09 | 0.05 |
| | | | -0.13 | -0.27 | -0.46 | -0.49 | -0.24 | -0.53 | -0.33 | 0.07 | -0.17 | -0.06 | 0.00 | -0.32 | -0.22 | -0.06 |
| 10000 MHz | 4745 | 69.9 | 208 | 551 | 885 | 1239 | 1608 | 1935 | 2295 | 2668 | 2997 | 3355 | 3699 | 4035 | 4393 | 4745 |
| | | | 9 | 2 | -13 | 9 | 10 | -13 | -3 | 21 | 8 | 6 | 3 | -11 | -3 | 8 |
| | | | 0.12 | 0.03 | -0.20 | -0.14 | 0.14 | -0.18 | -0.04 | 0.30 | 0.00 | 0.12 | 0.04 | -0.16 | -0.04 | 0.00 |
| | | | -0.56 | -0.64 | -0.86 | -0.79 | -0.50 | -0.82 | -0.66 | -0.32 | -0.60 | -0.48 | -0.55 | -0.73 | -0.61 | -0.56 |
| 14000 MHz | 4792 | 70.0 | 254 | 598 | 942 | 1284 | 1636 | 1967 | 2334 | 2712 | 3046 | 3402 | 3753 | 4087 | 4445 | 4783 |
| | | | 11 | 5 | -1 | -9 | -6 | -25 | -8 | 20 | 4 | 10 | 11 | -5 | 3 | -9 |
| | | | 0.16 | 0.08 | -0.01 | -0.12 | -0.09 | -0.36 | -0.12 | 0.28 | 0.05 | 0.14 | 0.15 | -0.07 | 0.04 | -0.13 |
| | | | 0.10 | 0.03 | -0.04 | -0.14 | -0.10 | -0.36 | -0.10 | 0.31 | 0.10 | 0.20 | 0.23 | 0.01 | 0.14 | -0.02 |
| 18000 MHz | 4798 | 68.9 | 332 | 666 | 1019 | 1365 | 1695 | 2019 | 2360 | 2730 | 3061 | 3413 | 3754 | 4094 | 4468 | 4834 |
| | | | 15 | 4 | 12 | 14 | -1 | -22 | -26 | 0 | -14 | -7 | -10 | -15 | 14 | 36 |
| | | | 0.21 | 0.06 | 0.18 | 0.20 | -0.02 | -0.32 | -0.37 | 0.00 | -0.20 | -0.10 | -0.15 | -0.22 | 0.21 | 0.52 |
| | | | 1.22 | 1.00 | 1.06 | 1.02 | 0.75 | 0.39 | 0.27 | 0.57 | 0.31 | 0.36 | 0.24 | 0.11 | 0.47 | 0.71 |

| RF Input Power (dBm) |
|----------------------------------|
| Measured Value (mV) |
| Error (mV) |
| LINEARITY ERROR (dB) 0.48 |
| ACCURACY ERROR (dB) -1.02 |



| |
|----------------------------------|
| Measured Value (mV) |
| Error (mV) |
| LINEARITY ERROR (dB) 0.29 |
| ACCURACY ERROR (dB) -0.53 |

| |
|----------------------------------|
| Measured Value (mV) |
| Error (mV) |
| LINEARITY ERROR (dB) 0.30 |
| ACCURACY ERROR (dB) -0.86 |

| |
|-----------------------------------|
| Measured Value (mV) |
| Error (mV) |
| LINEARITY ERROR (dB) -0.36 |
| ACCURACY ERROR (dB) -0.36 |

| |
|----------------------------------|
| Measured Value (mV) |
| Error (mV) |
| LINEARITY ERROR (dB) 0.52 |
| ACCURACY ERROR (dB) 1.22 |

| Flatness | +/- dB | 0.93 | 0.85 | 1.04 | 0.98 | 0.69 | 0.67 | 0.57 | 0.57 | 0.57 | 0.44 | 0.39 | 0.42 | 0.54 | 0.78 | 1.04 |
|----------|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
|----------|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|





Summary Data For ERDLVA-2G18G-65-70MV-70C



LOG TRANSFER WITH FREQUENCY

TESTED BY: Anton L.
 MODEL: ERDLVA-2G18G-65-70MV-70C
 SERIAL NO: PL48060/2444
 DATE: 10/30/2024

Test Temp: 70 °C
 Video Offset: 51 mV

| Frequency | | -65 | -60 | -55 | -50 | -45 | -40 | -35 | -30 | -25 | -20 | -15 | -10 | -5 | 0 | RF Input Power (dBm) |
|-----------|----------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|----------------------|
| 2000 MHz | INTERCEPT (mV) | 4912 | | | | | | | | | | | | | | Measured Value (mV) |
| | SLOPE (mV/dB) | 70.0 | | | | | | | | | | | | | | Error (mV) |
| | | 343 | 719 | 1060 | 1414 | 1779 | 2094 | 2452 | 2827 | 3163 | 3532 | 3897 | 4216 | 4546 | 4883 | LINEARITY ERROR (dB) |
| | | -20 | 6 | -3 | 1 | 16 | -19 | -11 | 15 | 1 | 20 | 35 | 4 | -16 | -29 | ACCURACY ERROR (dB) |
| | | -0.28 | 0.09 | -0.04 | 0.02 | 0.24 | -0.26 | -0.15 | 0.21 | 0.01 | 0.28 | 0.49 | 0.05 | -0.24 | -0.42 | |
| | | -0.19 | 0.21 | 0.09 | 0.16 | 0.39 | -0.10 | 0.02 | 0.39 | 0.20 | 0.49 | 0.71 | 0.28 | 0.00 | -0.17 | |
| 6000 MHz | INTERCEPT (mV) | 4920 | | | | | | | | | | | | | | Measured Value (mV) |
| | SLOPE (mV/dB) | 70.2 | | | | | | | | | | | | | | Error (mV) |
| | | 342 | 717 | 1064 | 1414 | 1773 | 2090 | 2458 | 2843 | 3178 | 3535 | 3872 | 4203 | 4554 | 4918 | LINEARITY ERROR (dB) |
| | | -18 | 6 | 2 | 2 | 10 | -24 | -7 | 28 | 12 | 18 | 4 | -16 | -15 | -2 | ACCURACY ERROR (dB) |
| | | -0.26 | 0.09 | 0.04 | 0.02 | 0.14 | -0.34 | -0.10 | 0.39 | 0.17 | 0.26 | 0.06 | -0.22 | -0.22 | -0.03 | |
| | | -0.19 | 0.18 | 0.15 | 0.16 | 0.30 | -0.16 | 0.11 | 0.62 | 0.42 | 0.53 | 0.35 | 0.09 | 0.12 | 0.33 | |
| 10000 MHz | INTERCEPT (mV) | 4852 | | | | | | | | | | | | | | Measured Value (mV) |
| | SLOPE (mV/dB) | 69.9 | | | | | | | | | | | | | | Error (mV) |
| | | 289 | 661 | 1011 | 1371 | 1729 | 2047 | 2404 | 2773 | 3113 | 3466 | 3790 | 4141 | 4490 | 4862 | LINEARITY ERROR (dB) |
| | | -33 | 0 | 1 | 12 | 20 | -11 | -3 | 19 | 7 | 11 | -14 | -13 | -13 | 10 | ACCURACY ERROR (dB) |
| | | -0.32 | 0.00 | 0.01 | 0.17 | 0.29 | -0.16 | -0.05 | 0.24 | 0.10 | 0.16 | -0.21 | -0.18 | -0.19 | 0.14 | |
| | | -0.94 | -0.62 | -0.61 | -0.45 | -0.33 | -0.78 | -0.66 | -0.38 | -0.51 | -0.46 | -0.82 | -0.80 | -0.80 | -0.47 | |
| 14000 MHz | INTERCEPT (mV) | 4884 | | | | | | | | | | | | | | Measured Value (mV) |
| | SLOPE (mV/dB) | 69.2 | | | | | | | | | | | | | | Error (mV) |
| | | 353 | 738 | 1090 | 1439 | 1787 | 2101 | 2460 | 2821 | 3155 | 3510 | 3840 | 4182 | 4523 | 4892 | LINEARITY ERROR (dB) |
| | | -33 | 6 | 12 | 15 | 17 | -15 | -2 | 13 | 1 | 10 | -6 | -10 | -15 | 8 | ACCURACY ERROR (dB) |
| | | -0.48 | 0.08 | 0.17 | 0.21 | 0.24 | -0.22 | -0.03 | 0.19 | 0.01 | 0.14 | -0.09 | -0.14 | -0.22 | 0.12 | |
| | | -0.03 | 0.48 | 0.52 | 0.52 | 0.50 | 0.00 | 0.14 | 0.31 | 0.09 | 0.17 | -0.10 | -0.21 | -0.33 | -0.04 | |
| 18000 MHz | INTERCEPT (mV) | 4851 | | | | | | | | | | | | | | Measured Value (mV) |
| | SLOPE (mV/dB) | 70.0 | | | | | | | | | | | | | | Error (mV) |
| | | 289 | 662 | 1010 | 1368 | 1702 | 2026 | 2382 | 2756 | 3105 | 3463 | 3782 | 4138 | 4494 | 4880 | LINEARITY ERROR (dB) |
| | | -11 | 12 | 10 | 18 | 2 | -24 | -18 | 5 | 4 | 12 | -19 | -13 | -7 | 29 | ACCURACY ERROR (dB) |
| | | -0.15 | 0.17 | 0.14 | 0.26 | 0.03 | -0.35 | -0.26 | 0.08 | 0.06 | 0.17 | -0.27 | -0.19 | -0.10 | 0.41 | |
| | | -0.94 | -0.60 | -0.62 | -0.50 | -0.71 | -1.08 | -0.98 | -0.62 | -0.63 | -0.50 | -0.93 | -0.84 | -0.74 | -0.21 | |

| | | | | | | | | | | | | | | | | |
|----------|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Flatness | +/- dB | 0.46 | 0.55 | 0.57 | 0.51 | 0.61 | 0.54 | 0.56 | 0.62 | 0.52 | 0.52 | 0.82 | 0.56 | 0.46 | 0.40 | 0.82 |
|----------|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|







**Summary Data
For
ERDLVA-2G18G-65-70MV-70C**

PL48060/2444

VSWR 1.81:1





TSS @ -71.8 dBm





Summary Data
For
ERDLVA-2G18G-65-70MV-70C



PL48060/2444





Summary Data
For
ERDLVA-2G18G-65-70MV-70C

PL48060/2444







**Summary Data
For
ERDLVA-2G18G-65-70MV-70C**

PL48060/2444

CW Immunity 1.49 ms



CW Recovery Plot





**Summary Data
For
ERDLVA-2G18G-65-70MV-70C**

PL48060/2444

RMS Noise 17.7 mV

