



TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2 TO 18 GHz (Optimized 12 – 18 GHz)	2 TO 18 GHz (Optimized 12 – 18 GHz)	PMI QA3
2	VSWR:	3.0: 1 Max @ -20dBm	2.5:1 (See Plot)	
3	Minimum Signal Level for Logic 1:	-20 dBm @ 2.0 GHz -17 dBm @ 18.0 GHz	-20 dBm @ 2.0 GHz -19dBm @ 18.0 GHz	
4	Threshold Variation over Frequency (Any 1 GHz Window)	± 0.5 dB	±0.5dB	
5	Minimum Signal Level for Logic 0	-25 dBm	-21dBm	
6	Dynamic Range:	+10 dBm Max	+10dBm	
7	Propagation Delay from 50% of an input of -20 dBm	15 ns Max	<15nS	
8	Propagation Delay from 50% of an input of +10 dBm	15 ns Max	<15nS	
9	Output Logic:	LVPECL Compatible	LVPECL Compatible	
10	DC Supply:	+15VDC @ 100 mA Max -15VDC @ 100 mA Max	+15VDC @88 mA -15VDC @ 47 mA	

7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com




**SUMMARY TEST DATA
ON
TD-30T-SHS-218-12G18G-PECL**

Threshold Variation at 25°C

Freq [GHz]	12 GHz	13 GHz	14 GHz	15 GHz	16 GHz	17 GHz	18 GHz	Variation
P-In [dBm]	-20	-20	-20	-20	-20	-19	-19	±0.5

VSWR Plot



QA/QC Approval: _____ Date: _____