

## SUMMARY TEST DATA ON PTP-3D2G-5D625G-9D5G-SFF

CUSTOMER: \_\_\_\_\_  
SO: \_\_\_\_\_  
MODEL NO: PTP-3D2G-5D625G-9D5G-SFF  
SERIAL NO: PL58126/2609

TESTED BY: EA Valdez  
TEMPERATURE: +25°C  
DATE: 2/25/2026  
DRAWING NO: 27649760 REV: A1

TEST ITEM NO:	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	QA/QC
1	Frequency Range	Band 1: 2.8-3.6 GHz Band 2: 5.25-6 GHz Band 3: 8.5-10.5 GHz	2.8-3.6 GHz 5.25-6 GHz 8.5-10.5 GHz	QA3 PMI
2	Insertion Loss	0.8dB Max	0.83 dB	
3	VSWR	1.8:1 Max	1.7:1	
4	Rejection (Band 1)	40 dB Min @ 5.25 - 6 GHz 50 dB Min @ 8.5 - 10.5 GHz	73.4 dB 71.6 dB	
5	Rejection (Band 2)	40 dB Min @ 2.8 - 3.6 GHz 40 dB Min @ 8.5 - 10.5 GHz	68.8 dB 73.2 dB	
6	Rejection (Band 3)	70 dB Min @ 2.8 - 3.6 GHz 40 dB Min @ 5.25 - 6 GHz	72.3 dB 62.8 dB	

QA/QC Approval: *K. Klamm*

Date: 2.27.26











