



SUMMARY TEST DATA
ON
LM-20M18G-100W-15DBM-TH-OPT618

Customer: _____
SO No: _____
Model No: LM-20M18G-100W-15DBM-TH-OPT618
Serial No: PL45230/2413

Tested By: John R.
Temperature: +25°C
Date: 3/27/2024
Drawing No: 27647080 REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	6 GHz to 18 GHz	6 GHz to 18 GHz	
2	Insertion Loss:	2.6 dB Max. @ -10 dBm Input Power	2.35 dB See Graph	
5	VSWR:	2.0:1 Max. @ -10 dBm Input Power	1.67:1 In 1.69:1 Out See Graph	
3	Leakage Power:	+15dBm Max. @ 100 W CW	Pass See Typical Characteristics	
4	Recovery Time (3 dB):	100 ns Max. 100 W Peak Power	Pass See Typical Characteristics	
6	RF Power Handling:	100 W CW Max.	Pass See Typical Characteristics	
		1kW PEAK Max. +85°C (1µs PULSE WIDTH, 0.1% DUTY CYCLE) 100W (1µs PULSE WIDTH, 1% DUTY CYCLE, 10 kHz) 100W (10 µs PULSE WIDTH, 0.1% DUTY CYCLE, 100 Hz) 100W (1µs PULSE WIDTH, 1% DUTY CYCLE, 1 kHz) 100W (40µs PULSE WIDTH, 1% DUTY CYCLE, 2.5 kHz)	Pass See Typical Characteristics	
7	Limiting Threshold:	+ 5 dBm Min. (1 dB Compression)	+ 6 dBm See Graph	

QA/QC Approval: _____

SUMMARY TEST DATA


ON

LM-20M18G-100W-15DBM-TH-OPT618


Date:

PL45230/2413

Insertion Loss



VSWR



Limiter Response with Frequency

