

**SUMMARY TEST DATA  
ON  
P8T-0D418-75-T-SFF-NG**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P8T-0D418-75-T-SFF-NG  
 Serial No: PL53111/2521

Tested By: S. O'Neill  
 Temperature: 25°C  
 Date: 5/22/2025  
 Drawing No: 27650320 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.4 GHz to 18 GHz	0.4 GHz to 18 GHz	
2	Isolation	75 dB Min.	80.6 dB	
3	Insertion Loss	3.4 dB Max., 0.4-10 GHz 4.5 dB Max., 10-18 GHz	2.82 dB 4.1 dB	
4	Return Loss (All Ports On Or Off)	-10 dB Min.	-12.05 dB J0 -11.37 dB J1-J8 -11.69 dB J1-J8 Off	
5	Power Supply	5 V @ 250 mA Max. -12 V @ 100 mA Max.	5 V @ 168 mA -12 V @ 75 mA	

QA/QC Approval: \_\_\_\_\_

Date: \_\_\_\_\_

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 Email: sales@quanticpmi.com



