


APTMP3-00010250-2015-D9

Features: (typical values)

- High Gain25 dB
- Super Low Noise Figure0.75 dB
- Output Power +22 dBm
- No External component required.
- Available in TO-8, SMT, Connectorize housing or per customer Requested Package
- **Available in +3V/5V/10V/12V/15V**

**10-2500 MHz
Wideband Amplifier
Gain Block
Super Low Cost
Super Low Noise**




Maximum Ratings

Storage Temperature	-62°C to +125°C
DC Voltage	+6 volts
RF Input Power	+10.0 dBm
Case Temperature	+100°C

Specifications (Referenced to 50 ohms)

Parameter	Typical Conditions	Min Value	Max Value	Units
Frequency		10	2500	MHz.
Gain at 2 GHz	20	16.0		dB.
Gain Var. over temp	0.6			ΔdB.
Pout @ 1dB Comp	+20	+15		dBm.
Noise Figure 20-2500MHz	1.0		2.0	dB.
Reverse Isolation	25			dB.
IP ₃ /IP ₂ (two-tone)*	35/45			dBm.
VSWR In/Out 20-2500 MHz	1.8:1		2.5:1	
Supply Required	+5/70		+5/75	v/mA.



Typical Performance Curves @ +25c

