



SUMMARY TEST DATA ON P2T-500M18G-50-T-SFF-I-SP

Customer: _____
 SO No: _____
 Model No: P2T-500M18G-50-T-SFF-I-SP
 Serial No: PL50628/2450

Tested By: K. Wagaman
 Temperature: +25° C
 Date: 12/10/2024
 Drawing No: 27633640 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	0.5 to 18.0 GHz	0.5 to 18.0 GHz	PMI QA4
2	Insertion Loss:	2.8 dB Max.	2.4 dB See Plot	
3	Isolation:	50 dB Min.	58 dB See Plot	
4	VSWR:	1.9:1 Max.	1.7:1 See Plot	
5	Input Power:	+23 dBm CW Max.	Pass See Typical Characteristics	
6	Switching Speed:	50 ns Max.	<40 ns See Typical Characteristics	
7	Controls: CTL1=J2 CTL2=J3	TTL "0" → Insertion Loss TTL "1" → Isolation	Pass	
8	DC Supply:	+5 VDC @ 80 mA -12 VDC @ 80 mA	27 mA 68 mA	

QA/QC Approval: *Cameron Kelum*

Date: 12/11/24

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@pmi-rf.com

**SUMMARY TEST DATA
ON
P2T-500M18G-50-T-SFF-I-SP**

